

SACB-6/12-M23 - Sensor/actuator box



1692828

<https://www.phoenixcontact.com/us/products/1692828>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator box, application: Standard, connection method: M12 socket Plastic, number of slots: 6, number of positions: 5, coding: A, slot assignment: Double, status display: No, Universal; master cable connection: M23 plug connection 90°, shielding: no

Your advantages

- Safety in the field, thanks to molded housing and high degree of protection
- Save space: distributor box with double occupancy for two sensors in one slot

Commercial data

Item number	1692828
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF41
Product key	BF3CBB
Catalog page	Page 114 (PC-2009)
GTIN	4017918177959
Weight per piece (including packing)	134.8 g
Weight per piece (excluding packing)	112.62 g
Customs tariff number	85366990
Country of origin	DE

SACB-6/12-M23 - Sensor/actuator box



1692828

<https://www.phoenixcontact.com/us/products/1692828>

Technical data

Notes

General	NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.
General	Unused slots are to be sealed off prior to commissioning. Suitable sealing elements are to be found under "Accessories".

Product properties

Product type	Distributor boxes with M8 to M12 slots
Number of positions	5
Application	Standard
Number of slots	6
Coding	A
LED	No

Material specifications

Material	PA
	PA
Flammability rating according to UL 94	V0
Seal material O-ring	NBR
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	PA
Material of contact, master cable side	CU alloy
Material of the contact carrier on the master cable side	PA
Material of contact surface, master cable side	gold-plated

Dimensions

Dimensional drawing	
Width	54 mm
Height	26 mm
Length	129 mm

Connection data

Conductor connection

SACB-6/12-M23 - Sensor/actuator box



1692828

<https://www.phoenixcontact.com/us/products/1692828>

Connection method	M23 plug connection
Tightening torque slot sensor/actuator cable	0.4 Nm

Pin assignment

Slot/position = Wire color or connection	1 / 4 (A) = 15
	1 / 2 (B) = 7
	2 / 4 (A) = 5
	2 / 2 (B) = 4
	3 / 4 (A) = 16
	3 / 2 (B) = 8
	4 / 4 (A) = 3
	4 / 2 (B) = 14
	5 / 4 (A) = 17
	5 / 2 (B) = 9
	6 / 4 (A) = 2
	6 / 2 (B) = 13
	1-6 / 1 (+ 120 V) = 19
	1-6 / 3 (0 V) = 6
	1-6 / 5 (PE) = 12

Signaling

Status display present	No
------------------------	----

Electrical properties

Max. operating voltage U_{\max}	135 V
Nominal voltage U_N	120 V AC
	120 V DC
Rated current, total	12 A
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	4 A

Cable/line

Sensor/actuator connection system	M12 socket
Connection method	M23 plug connection
Tightening torque slot sensor/actuator cable	0.4 Nm


Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-20 °C ... 75 °C

Drawings

Schematic diagram




M23 plug connection pin, 19-pos.

SACB-6/12-M23 - Sensor/actuator box

1692828

<https://www.phoenixcontact.com/us/products/1692828>

Circuit diagram




SACB-6/12-M23 - Sensor/actuator box

1692828

<https://www.phoenixcontact.com/us/products/1692828>



Dimensional drawing




SACB-6/12-M23 - Sensor/actuator box

1692828

<https://www.phoenixcontact.com/us/products/1692828>



Schematic diagram



M12 slot, socket, 5-pos.

SACB-6/12-M23 - Sensor/actuator box





1692828

<https://www.phoenixcontact.com/us/products/1692828>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1692828>

	cUL Recognized			
	Approval ID: FILE E 118976			
		Nominal voltage U_N	Nominal current I_N	Cross section AWG
		120 V	-	22 - 16
				Cross section mm ²
				-

	UL Recognized			
	Approval ID: FILE E 118976			
		Nominal voltage U_N	Nominal current I_N	Cross section AWG
		120 V	-	22 - 16
				Cross section mm ²
				-

	EAC
	Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

SACB-6/12-M23 - Sensor/actuator box



1692828

<https://www.phoenixcontact.com/us/products/1692828>

Classifications

ECLASS

ECLASS-11.0	27440111
ECLASS-12.0	27440111
ECLASS-13.0	27440111

ETIM

ETIM 8.0	EC003558
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SACB-6/12-M23 - Sensor/actuator box



1692828

<https://www.phoenixcontact.com/us/products/1692828>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

SACB-6/12-M23 - Sensor/actuator box



1692828

<https://www.phoenixcontact.com/us/products/1692828>

Accessories

RCK-TGUM/BL16+3/ 5,0PUR-U - Master cable

1684056

<https://www.phoenixcontact.com/us/products/1684056>



Master cable, application: Sensor/actuator box, connection method: M12 socket Plastic, number of positions: 19, slot assignment: Double, status display: No; master cable connection: M23 plug connection, PUR/PVC, cable length: 5 m, shielding: no, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1260765

RCK-TGUM/BL16+3/10,0PUR-U - Master cable

1684069

<https://www.phoenixcontact.com/us/products/1684069>



Master cable, application: Sensor/actuator box Plastic, number of positions: 19, slot assignment: Double, status display: No; master cable connection: M23 plug connection, PUR/PVC, cable length: 10 m, shielding: no, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1260764

SACB-6/12-M23 - Sensor/actuator box



1692828

<https://www.phoenixcontact.com/us/products/1692828>

RCK-TWUM/BL16+3/ 5,0PUR-U - Master cable

1684072

<https://www.phoenixcontact.com/us/products/1684072>



Master cable, application: Sensor/actuator box, connection method: M12 socket Plastic, number of positions: 19, slot assignment: Double, status display: No; master cable connection: M23 plug connection, PUR/PVC, cable length: 5 m, shielding: no, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1260753

RCK-TWUM/BL16+3/10,0PUR-U - Master cable

1684085

<https://www.phoenixcontact.com/us/products/1684085>



Master cable, application: Sensor/actuator box, connection method: M12 socket Plastic, number of positions: 19, slot assignment: Double, status display: No; master cable connection: M23 plug connection, PUR/PVC, cable length: 10 m, shielding: no, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1260752

SACB-6/12-M23 - Sensor/actuator box

1692828

<https://www.phoenixcontact.com/us/products/1692828>



V-RC/TGUM 13/KVD 13/LBL 16+3 - Cable connector

1000042

<https://www.phoenixcontact.com/us/products/1000042>



Cable connector, number of positions: 19, status display: No; master cable connection: M23 screw locking, shielding: no, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1237971

V-RC/TWUM 13/KVD 13/LBL 16+3 - Cable connector

1000044

<https://www.phoenixcontact.com/us/products/1000044>



Cable connector, number of positions: 19, status display: No; master cable connection: M23 screw locking, shielding: no, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1237973

SACB-6/12-M23 - Sensor/actuator box



1692828

<https://www.phoenixcontact.com/us/products/1692828>

PROT-M12 - Screw plug

1680539

<https://www.phoenixcontact.com/us/products/1680539>



An M12 screw plug for the unoccupied M12 sockets of the sensor/actuator cable, boxes and flush-type connectors

MSK 1 - Metal protective cap

1665897

<https://www.phoenixcontact.com/us/products/1665897>



Metal protective cap, degree of protection: IP67, when in locked state, color: silver, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1245640

SACB-6/12-M23 - Sensor/actuator box

1692828

<https://www.phoenixcontact.com/us/products/1692828>



MSK 2 - Protective cap

1665907

<https://www.phoenixcontact.com/us/products/1665907>

Protective cap, degree of protection: IP67, when in locked state, color: silver,
Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%)
item no.: 1245641



KSK 1 - Sealing cap

1685013

<https://www.phoenixcontact.com/us/products/1685013>

Plastic sealing cap, for unoccupied M23 connectors



SACB-6/12-M23 - Sensor/actuator box

1692828

<https://www.phoenixcontact.com/us/products/1692828>



ZBN 18:UNBEDRUCKT - Zack marker strip

2809128

<https://www.phoenixcontact.com/us/products/2809128>



Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 18 mm, lettering field size: 18 x 5 mm, Number of individual labels: 5

PLUSCON-RCS - Pipe spanner

1665062

<https://www.phoenixcontact.com/us/products/1665062>



Pipe spanner

SACB-6/12-M23 - Sensor/actuator box

1692828

<https://www.phoenixcontact.com/us/products/1692828>



TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

SAC BIT M12-D15 - Tool

1208432

<https://www.phoenixcontact.com/us/products/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

SACB-6/12-M23 - Sensor/actuator box

1692828

<https://www.phoenixcontact.com/us/products/1692828>



SACC BIT M12-D20 - Tool

1208445

<https://www.phoenixcontact.com/us/products/1208445>

Nut for assembling M12 connectors for assembly with a knurl diameter of 20 mm, for 4 mm hexagonal drive



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com