

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, Variable cable type, shielded, free cable end, on Socket angled M12, coding: A, cable length: Free input (0.2 ... 40.0 m)

Your advantages

- Easy and safe: 100% electrically tested plug-in components
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

Commercial data

Item number	1697454
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF17
Product key	BF1CIA
Catalog page	Page 193 (C-2-2019)
Customs tariff number	85444290
Country of origin	PL

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

Technical data

Product properties

Product type	Sensor/actuator cable
Number of positions	3
Application	Standard
No. of cable outlets	1
Shielded	yes
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Contact resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A
Protective circuit	unwired

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Signaling

Status display	No
Status display present	No

Connection data

Conductor connection

Tightening torque	0.4 Nm (M12 connector)
-------------------	------------------------

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

Connector

Connection 1

Type	free cable end
------	----------------


Connection 2

Type	Socket angled M12
Number of positions	3
Coding type	A
Number of positions	3

Cable/line

Cable length	Free input (0.2 ... 40.0 m)
--------------	-----------------------------

PUR/PVC shielded, gray [100]

Dimensional drawing	
Shielded	yes
Cable weight	38 kg/km
Cable type	PUR/PVC shielded, gray
Short symbol	LiYV1CY11Y
Cable type (abbreviation)	100
External cable diameter	5.2 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	gray RAL 7001
Material, inner sheath	PVC
Conductor material	Bare Cu litz wires
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	0.34 mm²
Material wire insulation	PVC
Thickness, insulation	≥ 0.23 mm (Core insulation)
Wire diameter incl. insulation	1.5 mm ±0.05 mm
Single wire, color	brown, blue, black
Overall twist	3 wires, twisted
Shielding	Braided copper wires
Optical shield covering	85 %
Nominal voltage, cable	≤ 300 V

SAC-3P-M12FR SH/.../... - Sensor/actuator cable




1697454

<https://www.phoenixcontact.com/us/products/1697454>

Test voltage Core/Shield	≥ 2000 V
Test voltage, cable	≥ 3000 V
Cable resistance	max. 58 Ω/km (at 20 °C)
Cable insulation resistance	≥ 100 MΩ*km (at 20 °C)
Smallest bending radius, fixed installation	52 mm
Smallest bending radius, movable installation	52 mm
Number of bending cycles	2000000
Bending radius	52 mm
Traversing path	5 m
Traversing rate	3 m/s
Resistance to oil	in accordance with DIN EN 60811-2-1
Ambient temperature (operation)	-5 °C ... 80 °C (Cable, flexible installation)
	-25 °C ... 80 °C (cable, fixed installation)

PVC gray [500]

Dimensional drawing	
Shielded	yes
Cable weight	40 kg/km
Cable type	PVC gray
Cable type (abbreviation)	500
External cable diameter	5.2 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	gray RAL 7001
Conductor material	Bare Cu litz wires
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	0.34 mm²
Material wire insulation	PVC
Thickness, insulation	≥ 0.23 mm (Core insulation)
Wire diameter incl. insulation	1.4 mm ±0.02 mm
Single wire, color	brown, blue, black
Overall twist	3 wires, twisted
Shielding	Tinned copper braided shield
Optical shield covering	85 %
Nominal voltage, cable	≤ 300 V
Test voltage, cable	≥ 3000 V
Cable resistance	max. 58 Ω/km (at 20 °C)

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

Cable insulation resistance	$\geq 1 \text{ G}\Omega \cdot \text{km}$ (at 20 °C)
Resistance to oil	in accordance with DIN EN 60811-2-1
Ambient temperature (operation)	-5 °C ... 80 °C (Cable, flexible installation)
	-25 °C ... 80 °C (cable, fixed installation)

PUR halogen-free black [PUR]

Shielded	yes
UL AWM Style	20549
Cable weight	31 kg/km
Cable type	PUR halogen-free black
Short symbol	Li9Y-VI-C-VI-11Y
Cable type (abbreviation)	PUR
External cable diameter	4.65 mm \pm 0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	3x 0.34 mm ² (Signal line)
Material wire insulation	PP
Thickness, insulation	$\geq 0.21 \text{ mm}$ (Core insulation)
Wire diameter incl. insulation	1.27 mm \pm 0.02 mm (Signal line)
Single wire, color	brown, blue, black
Overall twist	3 wires, twisted
Shielding	Braided copper wires
Optical shield covering	80 %
Nominal voltage, cable	$\leq 300 \text{ V}$
Test voltage, cable	$\geq 3000 \text{ V}$
Cable resistance	max. 58 Ω /km (at 20 °C)
Cable insulation resistance	$\geq 100 \text{ G}\Omega \cdot \text{km}$ (at 20 °C)
Smallest bending radius, fixed installation	23 mm
Smallest bending radius, movable installation	47 mm
Number of bending cycles	10000000
Bending radius	47 mm
Traversing path	10 m
Traversing rate	3 m/s
Acceleration	10 m/s ²
Halogen-free	in accordance with DIN VDE 0472 part 815
Resistance to oil	in accordance with DIN EN 60811-2-1
Flame resistance	in accordance with UL 758/1581 FT2
	DIN EN 60332-2-2 (20 s)
Other resistance	Highly resistant to acids, alkaline solutions and solvents
	hydrolysis and microbe resistant
	partly UV-resistant in accordance with DIN EN ISO 4892-2-A

SAC-3P-M12FR SH/.../... - Sensor/actuator cable




1697454

<https://www.phoenixcontact.com/us/products/1697454>

Special properties	Flexible cable conduit capable
	Silicone-free
	Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	-25 °C ... 80 °C (Cable, flexible installation)
	-40 °C ... 80 °C (cable, fixed installation)

PVC shielded black [PVC]

Dimensional drawing	
Shielded	yes
Cable weight	40 kg/km
Cable type	PVC shielded black
Cable type (abbreviation)	PVC
External cable diameter	5.2 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	3x 0.34 mm² (Signal line)
Material wire insulation	PVC
Thickness, insulation	≥ 0.23 mm (Core insulation)
Wire diameter incl. insulation	1.4 mm ±0.02 mm
Single wire, color	brown, blue, black
Overall twist	3 wires, twisted
Shielding	Tinned copper braided shield
Optical shield covering	85 %
Nominal voltage, cable	≤ 300 V
Test voltage, cable	≥ 3000 V
Cable resistance	max. 58 Ω/km (at 20 °C)
Cable insulation resistance	≥ 100 MΩ*km (at 20 °C)
Resistance to oil	in accordance with DIN EN 60811-2-1
Flame resistance	As per UL-Style 2464
Ambient temperature (operation)	-5 °C ... 80 °C (Cable, flexible installation)
	-25 °C ... 80 °C (cable, fixed installation)

Environmental and real-life conditions

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

Standards and regulations


Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

1697454

<https://www.phoenixcontact.com/us/products/1697454>

Drawings

Diagram




SAC-3P-M12FR SH/.../... - Sensor/actuator cable

1697454

<https://www.phoenixcontact.com/us/products/1697454>




Dimensional drawing



M12 x 1 socket, angled, shielded

Schematic diagram



Pin assignment M12 socket, 3-pos., A-coded, view female side


SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

Circuit diagram



SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1697454>



EAC

Approval ID: RU C-DE.BL08.B.00286



UL Listed

Approval ID: FILE E 221474

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	300 V	4 A	-	-



cUL Listed

Approval ID: FILE E 221474

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	300 V	4 A	-	-



EAC-RoHS

Approval ID: RU D-DE.HB35.B.00387

cULus Listed

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

ETIM

ETIM 8.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

Accessories

UCT-WMT (23X4) - Conductor marker

0801453

<https://www.phoenixcontact.com/us/products/0801453>



Conductor marker, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 30

UC-WMT (23X4) - Conductor marker

0819411

<https://www.phoenixcontact.com/us/products/0819411>



Conductor marker, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 24

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

US-WMT (23X4) - Cable marker

0828769

<https://www.phoenixcontact.com/us/products/0828769>



Cable marker, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 56

WMTW (23X4)R - Cable marker

0831004

<https://www.phoenixcontact.com/us/products/0831004>



Cable marker, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: insert, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 3000

SAC-3P-M12FR SH/.../... - Sensor/actuator cable

1697454

<https://www.phoenixcontact.com/us/products/1697454>



B-STIFT - Marker pen

1051993

<https://www.phoenixcontact.com/us/products/1051993>



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

CUTFOX-S VDE - Diagonal cutter

1212207

<https://www.phoenixcontact.com/us/products/1212207>



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

WIREFOX SAC-1 - Stripping tool

1212757

<https://www.phoenixcontact.com/us/products/1212757>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 3.2 to 4.4 mm, any stripping length

WIREFOX SAC - Stripping tool

1212623

<https://www.phoenixcontact.com/us/products/1212623>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

SAC-3P-M12FR SH/.../... - Sensor/actuator cable

1697454

<https://www.phoenixcontact.com/us/products/1697454>



WIREFOX 10 - Stripping tool

1212150

<https://www.phoenixcontact.com/us/products/1212150>



Stripping tool, for cables and conductors from 0.02 - 10 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

WP-CTA POM 13,0 BK - Protective hose adapter

1422884

<https://www.phoenixcontact.com/us/products/1422884>



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

WP-PA HF 13,0 BK - Protective hose

3240681

<https://www.phoenixcontact.com/us/products/3240681>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: V0, inner diameter: 10 mm, Total length: 50 m

WP-PA HF-HB 13,0 BK - Protective hose

3240839

<https://www.phoenixcontact.com/us/products/3240839>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: HB, inner diameter: 10 mm, Total length: 50 m

SAC-3P-M12FR SH/.../... - Sensor/actuator cable

1697454

<https://www.phoenixcontact.com/us/products/1697454>



PROT-M12 MS-PA-CHAIN - Screw plug

1430899

<https://www.phoenixcontact.com/us/products/1430899>

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



SAC-M12-EXCLIP-F - Locking clip

1558991

<https://www.phoenixcontact.com/us/products/1558991>

Locking clip for the socket side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools



SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

TSD-M 1,2NM - Torque screwdriver

1212224

<https://www.phoenixcontact.com/us/products/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

SAC-3P-M12FR SH/.../... - Sensor/actuator cable



1697454

<https://www.phoenixcontact.com/us/products/1697454>

TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

SAC BIT M12-D15 - Tool

1208432

<https://www.phoenixcontact.com/us/products/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com