

RF-12S1N8A80DU - Cable connector



1607276

<https://www.phoenixcontact.com/us/products/1607276>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable connector, straight, Screw locking mechanism, M23, number of positions: 12, contact connection type: Socket, shielded: yes, degree of protection: IP67, cable diameter range: 5 mm . .. 13.2 mm, number of positions: 12, connection method: Crimp connection, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1242261

Commercial data

Item number	1607276
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB33
Product key	ABRAGA
Catalog page	Page 78 (PC-2011)
GTIN	4046356174343
Weight per piece (including packing)	100.75 g
Weight per piece (excluding packing)	50.27 g
Customs tariff number	85366990
Country of origin	DE

RF-12S1N8A80DU - Cable connector



1607276

<https://www.phoenixcontact.com/us/products/1607276>

Technical data

Notes

General	Order crimp contacts Ø 1 mm separately
---------	--

Mounting

Connection method	Crimp connection
-------------------	------------------

Product properties

Product type	Circular connector (cable-side)
Number of positions	12
Connection profile	12
Application	Feedback, signal
	Signal
Series	RF
Shielded	yes
Coding	N
Thread type	M23

Material specifications

Seal material	FPM
Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material	PA 6.6
Gasket and O-ring material	FPM
Housing material	Metal

Connection data

Conductor connection	
Connection method	Crimp connection

Electrical properties

Contact	
Contact diameter	1 mm
Max. current	8 A
Nominal voltage U _N	48 V AC 74 V DC
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV

Connector

Type	straight
Direction of rotation	Standard

RF-12S1N8A80DU - Cable connector



1607276

<https://www.phoenixcontact.com/us/products/1607276>

Cable/line

External cable diameter	5 mm ... 13.2 mm
-------------------------	------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 125 °C
Altitude	2000 m


RF-12S1N8A80DU - Cable connector

1607276

<https://www.phoenixcontact.com/us/products/1607276>


Drawings

Dimensional drawing



RF-12(17)...N8A80DU

Schematic diagram



RF-12S1N8A80DU - Cable connector





1607276

<https://www.phoenixcontact.com/us/products/1607276>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1607276>

 cUL Recognized Approval ID: FILE E 153698				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	48 V	5 A	- 20	-

 UL Recognized Approval ID: FILE E 153698				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	48 V	5 A	- 20	-

cULus Recognized				
-------------------------	--	--	--	--

RF-12S1N8A80DU - Cable connector



1607276

<https://www.phoenixcontact.com/us/products/1607276>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

RF-12S1N8A80DU - Cable connector



1607276

<https://www.phoenixcontact.com/us/products/1607276>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

RF-12S1N8A80DU - Cable connector



1607276

<https://www.phoenixcontact.com/us/products/1607276>

Accessories

SF-6CS2000 - Crimp contact

1605562

<https://www.phoenixcontact.com/us/products/1605562>



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: 0.06 mm² ... 0.25 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241922

SF-10KS004 - Crimp contact

1607356

<https://www.phoenixcontact.com/us/products/1607356>



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm² ... 0.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241922

RF-12S1N8A80DU - Cable connector



1607276

<https://www.phoenixcontact.com/us/products/1607276>

SF-6AS2000 - Crimp contact

1605557

<https://www.phoenixcontact.com/us/products/1605557>



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: 0.25 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241922

SF-10KS010 - Crimp contact

1605481

<https://www.phoenixcontact.com/us/products/1605481>



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241922

RF-12S1N8A80DU - Cable connector

1607276

<https://www.phoenixcontact.com/us/products/1607276>



SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/us/products/1607456>

Torque screwdriver, series: RC



SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/us/products/1607455>

Hook wrench, series: RC



RF-12S1N8A80DU - Cable connector

1607276

<https://www.phoenixcontact.com/us/products/1607276>



RF-Z0003 - Square mounting flange

1607905

<https://www.phoenixcontact.com/us/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1242369

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com