

DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



The VARIOFACE feed-through module implements a 1:1 connection between screw connection terminal blocks and an IDC/FLK pin strip (2.54 mm, number of positions: 34).

Commercial data

Item number	2280268
Packing unit	1 pc
Minimum order quantity	5 pc
Note	Made to order (non-returnable)
Sales key	C422
Product key	CK2215
Catalog page	Page 582 (C-7-2015)
GTIN	4017918054373
Weight per piece (including packing)	108.4 g
Weight per piece (excluding packing)	108.4 g
Customs tariff number	85369010
Country of origin	DE

DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>



Technical data

Product properties

Product type	Interface module
Product family	VARIOFACE
Number of positions	34
Operating mode	100% operating factor

Insulation characteristics

Insulation	Functional insulation
------------	-----------------------

Insulation characteristics: Air clearances and creepage distances

Insulation	Functional insulation
Overvoltage category	II
Pollution degree	2

Electrical properties

Operating voltage (AC)	≤ 30 V AC
Operating voltage (DC)	≤ 60 V DC
Current (per branch)	≤ 1 A
Current (Total current)	≤ 34 A (50 °C)

Air clearances and creepage distances

Rated insulation voltage	63 V
Rated surge voltage	0.6 kV (1.2/50 µs)

Connection data

Connection 1 (control level)

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK pin strip
Number of connections	1
Number of positions	34
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Connection 2 (field level)

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Number of positions	34
Conductor cross section rigid	0.2 mm² ... 4 mm²
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	24 ... 12

Signaling

DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>



Status display present	No
------------------------	----

Dimensions

Item dimensions

Width	39.88 mm
Height	103.4 mm
Depth	47.24 mm

Material specifications

Housing insulation material	Polyamide 6.6 green
-----------------------------	---------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection (Module)	IP20
Degree of protection (Installation location)	≥ IP54
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Altitude	≤ 2000 m

Approvals

UKCA

Certificate	UKCA-compliant
-------------	----------------

Standards and regulations

Air clearances and creepage distances

Standards/regulations	EN IEC 60664-1
-----------------------	----------------

Mounting

Mounting type	Rear mounting
Mounting position	any

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

DFLK 34 - Interface module


2280268

<https://www.phoenixcontact.com/us/products/2280268>




Drawings

Dimensional drawing



Dimensional drawing




DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>



Dimensional drawing



DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>



Classifications

ECLASS

ECLASS-11.0	27141152
ECLASS-13.0	27141152
ECLASS-12.0	27141152

ETIM

ETIM 8.0	EC002780
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>




Accessories

FLK EZ-DR.../.../... - Cable

2295059

<https://www.phoenixcontact.com/us/products/2295059>

Round cable, with preassembly, not shielded, variable cable length



FLK 34/EZ-DR/ 50/KONFEK - Cable

2299479

<https://www.phoenixcontact.com/us/products/2299479>

Round cable set; connection 1: IDC/FLK socket strip (1x 34-position); connection 2: IDC/FLK socket strip (1x 34-position); cable length: 0.5 m



DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>



FLK 34/EZ-DR/ 100/KONFEK - Cable

2299482

<https://www.phoenixcontact.com/us/products/2299482>



Round cable set; connection 1: IDC/FLK socket strip (1x 34-position); connection 2: IDC/FLK socket strip (1x 34-position); cable length: 1 m

FLK 34/EZ-DR/ 150/KONFEK - Cable

2299495

<https://www.phoenixcontact.com/us/products/2299495>



Round cable set; connection 1: IDC/FLK socket strip (1x 34-position); connection 2: IDC/FLK socket strip (1x 34-position); cable length: 1.5 m

DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>



FLK 34/EZ-DR/ 200/KONFEK - Cable

2299505

<https://www.phoenixcontact.com/us/products/2299505>



Round cable set; connection 1: IDC/FLK socket strip (1x 34-position); connection 2: IDC/FLK socket strip (1x 34-position); cable length: 2 m

FLK 34/EZ-DR/ 300/KONFEK - Cable

2299518

<https://www.phoenixcontact.com/us/products/2299518>



Round cable set; connection 1: IDC/FLK socket strip (1x 34-position); connection 2: IDC/FLK socket strip (1x 34-position); cable length: 3 m

DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>



FLK 34/EZ-DR/ 400/KONFEK - Cable

2299521

<https://www.phoenixcontact.com/us/products/2299521>



Round cable set; connection 1: IDC/FLK socket strip (1x 34-position); connection 2: IDC/FLK socket strip (1x 34-position); cable length: 4 m

FLK 34/EZ-DR/ 600/KONFEK - Cable

2299534

<https://www.phoenixcontact.com/us/products/2299534>



Round cable set; connection 1: IDC/FLK socket strip (1x 34-position); connection 2: IDC/FLK socket strip (1x 34-position); cable length: 6 m

DFLK 34 - Interface module

2280268

<https://www.phoenixcontact.com/us/products/2280268>



FLK 34/EZ-DR/ 800/KONFEK - Cable

2299547

<https://www.phoenixcontact.com/us/products/2299547>



Round cable set; connection 1: IDC/FLK socket strip (1x 34-position); connection 2: IDC/FLK socket strip (1x 34-position); cable length: 8 m

FLK 34/EZ-DR/1000/KONFEK - Cable

2299550

<https://www.phoenixcontact.com/us/products/2299550>



Round cable set; connection 1: IDC/FLK socket strip (1x 34-position); connection 2: IDC/FLK socket strip (1x 34-position); cable length: 10 m

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com