

UEG 30/1 - Electronic housing

2790871

<https://www.phoenixcontact.com/us/products/2790871>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Electronic housing, for PCB insertion, fully equipped with 4 screw or tab connections per side



Commercial data

Item number	2790871
Packing unit	1 pc
Minimum order quantity	10 pc
Sales key	AC11
Product key	ACHCCA
Catalog page	Page 723 (C-1-2013)
GTIN	4017918072360
Weight per piece (including packing)	60.7 g
Weight per piece (excluding packing)	60.7 g
Customs tariff number	85369010
Country of origin	DE

Technical data


Product properties

Type	Connection system integrated, housing closed
Product type	Complete housing
Product family	UEG
Number of positions	8
Pitch	5 mm
Number of rows	2
Housing type	Component housing
Housing series	UEG
Pin layout	Linear pinning

Electrical properties

Nominal voltage U_N	500 V (Voltage and current values are affected by the configuration of the printed circuit board.)
Nominal current I_N	10 A

Dimensions

Dimensional drawing	
Width	30 mm
Installed height	70 mm
Height NS 35/7,5	70 mm
Depth	79.5 mm
Length	79.5 mm
Pitch	5 mm

Material specifications

Color	green
Flammability rating according to UL 94	V0
Surface characteristics	untreated
Housing material	Polyamide

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 105 °C

UEG 30/1 - Electronic housing

2790871

<https://www.phoenixcontact.com/us/products/2790871>



Mounting

Mounting type	Soldering
Pin layout	Linear pinning
Connection method	Screw connection

UEG 30/1 - Electronic housing


2790871

<https://www.phoenixcontact.com/us/products/2790871>



Drawings

Dimensional drawing




UEG 30/1 - Electronic housing

2790871

<https://www.phoenixcontact.com/us/products/2790871>




Dimensional drawing




UEG 30/1, enlarged internal area, with 1 PCB, up to max. 8 positions

Dimensional drawing



Schematic diagram




UEG 30/1 - Electronic housing

2790871

<https://www.phoenixcontact.com/us/products/2790871>



Exploded view



UEG 30/1 - Electronic housing


2790871

<https://www.phoenixcontact.com/us/products/2790871>



Approvals

📄 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2790871>

 cULus Recognized Approval ID: E60425-19770427				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B				
	300 V	10 A	30 - 12	-
Use group D				
	300 V	10 A	30 - 12	-

UEG 30/1 - Electronic housing

2790871

<https://www.phoenixcontact.com/us/products/2790871>



Classifications

ECLASS

ECLASS-11.0	27182702
ECLASS-13.0	27190101

ETIM

ETIM 8.0	EC001031
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

UEG 30/1 - Electronic housing



2790871

<https://www.phoenixcontact.com/us/products/2790871>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

UEG 30/1 - Electronic housing

2790871

<https://www.phoenixcontact.com/us/products/2790871>



Accessories

DB 50- 90 GY - Wire bridge

2820929

<https://www.phoenixcontact.com/us/products/2820929>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: gray



Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com