

# EMG 45-DIO14M - Diode block



2950129

<https://www.phoenixcontact.com/us/products/2950129>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Diode module, with 14 diodes, common anode, diode type 1N 4007

## Your advantages

- Electrical decoupling of messages in fault reporting systems
- Spark-suppression diodes for limiting surge voltages of inductive loads

## Commercial data

Item number	2950129
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C440
Product key	CK4M11
Catalog page	Page 266 (C-5-2019)
GTIN	4017918083977
Weight per piece (including packing)	88.16 g
Weight per piece (excluding packing)	88.16 g
Customs tariff number	85411000
Country of origin	DE

# EMG 45-DIO14M - Diode block

2950129

<https://www.phoenixcontact.com/us/products/2950129>



## Technical data

### Product properties

Product type	Diode module
Insulation characteristics	
Pollution degree	2

### Input data

Diode	
Description of the input	14 diodes, common anode
Diode type	1 N 4007
Max. operating voltage $U_{max}$	250 V AC
Peak reverse voltage per diode	1300 V
Reverse current per diode	5 $\mu$ A
Conducting state voltage per diode	approx. 0.8 V
Conducting state current per diode	0.7 A (with single load)
	0.2 A (with simultaneous loads)

### Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

### Dimensions

Width	45 mm
Height	75 mm
Depth	55 mm

### Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

### Approvals

CE	
Certificate	CE-compliant
Note	and EN 61326

### Standards and regulations

# EMG 45-DIO14M - Diode block



2950129

<https://www.phoenixcontact.com/us/products/2950129>


Standards/regulations	DIN EN 50178
-----------------------	--------------

## Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

## Drawings

Circuit diagram



# EMG 45-DIO14M - Diode block

2950129

<https://www.phoenixcontact.com/us/products/2950129>



## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2950129>



**EAC**

Approval ID: RU\*DE\*08.B.01841/19

# EMG 45-DIO14M - Diode block

2950129

<https://www.phoenixcontact.com/us/products/2950129>



## Classifications

### ECLASS

ECLASS-11.0	27371010
ECLASS-12.0	27371010
ECLASS-13.0	27371010

### ETIM

ETIM 8.0	EC000683
----------	----------

### UNSPSC

UNSPSC 21.0	32151500
-------------	----------

# EMG 45-DIO14M - Diode block

2950129

<https://www.phoenixcontact.com/us/products/2950129>



## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

# EMG 45-DIO14M - Diode block

2950129

<https://www.phoenixcontact.com/us/products/2950129>



## Accessories

### EMG-GKS 12 - Marking material

2947035

<https://www.phoenixcontact.com/us/products/2947035>



Device marking label, width: 12 mm, area: 12 x 8 mm, e.g. for EML(10x7) R adhesive marking material

---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)