

UM108-SEFE/L - Lateral element



2959696

<https://www.phoenixcontact.com/us/products/2959696>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Side element with foot, 5 mm wide (left), for mounting on NS 32 or NS 35/7.5. PCB width: 107.5 mm



Your advantages

- Easy installation
- Flexible size and shape
- Inexpensive as a result of reducing the number of separate housing parts

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 2959696 |
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| Sales key | AC13 |
| Product key | ACHDBA |
| Catalog page | Page 757 (C-1-2013) |
| GTIN | 4017918086343 |
| Weight per piece (including packing) | 8.88 g |
| Weight per piece (excluding packing) | 8.36 g |
| Customs tariff number | 85389099 |
| Country of origin | PL |

UM108-SEFE/L - Lateral element



2959696

<https://www.phoenixcontact.com/us/products/2959696>

Technical data

Product properties

| | |
|------------------------------|---|
| Product type | Panel mounting base side part |
| Product family | UM108 |
| Type | Side element (left) with mounting foot for the DIN rail |
| Housing type | Press-drawn section housings |
| Ventilation openings present | no |
| Housing series | UM |

Dimensions

| | |
|-------|----------|
| Depth | 122.6 mm |
|-------|----------|

Material specifications

| | |
|--|--------------|
| Color | green (6021) |
| Flammability rating according to UL 94 | V0 |
| Surface characteristics | untreated |
| Housing material | Polyamide |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|--|
| Ambient temperature (operation) | -40 °C ... 105 °C (depending on power dissipation) |
|---------------------------------|--|

UM108-SEFE/L - Lateral element



2959696

<https://www.phoenixcontact.com/us/products/2959696>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2959696>



EAC

Approval ID: B.01687



UL Recognized

Approval ID: FILE E 240868

UM108-SEFE/L - Lateral element



2959696

<https://www.phoenixcontact.com/us/products/2959696>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27182701 |
| ECLASS-13.0 | 27190602 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC002779 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

UM108-SEFE/L - Lateral element



2959696

<https://www.phoenixcontact.com/us/products/2959696>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values |
|------------|---|

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com