

REL-IRG 24 - Single relay

2960261

<https://www.phoenixcontact.com/us/products/2960261>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Industrial relay, size 1, contact: 4 changeover contacts, input voltage 24 V DC



Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 2960261 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | C460 |
| Product key | CK6193 |
| Catalog page | Page 105 (IF-2002) |
| GTIN | 4017918086671 |
| Weight per piece (including packing) | 39.37 g |
| Weight per piece (excluding packing) | 36.079 g |
| Customs tariff number | 85364190 |
| Country of origin | JP |

REL-IRG 24 - Single relay

2960261

<https://www.phoenixcontact.com/us/products/2960261>



Technical data

Product properties

| | |
|-------------------------|--------------------------------|
| Product type | Single relay |
| Operating mode | 100% operating factor |
| Mechanical service life | approx. 5×10^7 cycles |

Insulation characteristics

| | |
|----------------------|----|
| Overvoltage category | II |
| Pollution degree | 2 |

Electrical properties

| | |
|--|--|
| Maximum power dissipation for nominal condition | 0.91 W |
| Test voltage (Winding/contact) | 2 kV AC (50 Hz, 1 min., winding/contact) |
| Test voltage (Changeover contact/changeover contact) | 2 kV AC (50 Hz, 1 min., changeover contact/changeover contact) |

Input data

Coil side

| | |
|---|------------------------|
| Nominal input voltage U_N | 24 V DC |
| Input voltage range | 18.7 V DC ... 36 V DC |
| Input voltage range in reference to U_N | see diagram |
| Drive and function | monostable |
| Drive (polarity) | non-polarized |
| Typical input current at U_N | 38 mA |
| Typical response time | 13 ms |
| Typical release time | 8 ms |
| Coil resistance | $630 \Omega \pm 15 \%$ |

Output data

Switching

| | |
|---------------------------------------|---------------------------------------|
| Contact switching type | 4 changeover contacts |
| Type of switch contact | Single contact |
| Contact material | AgNi, hard gold-plated |
| Maximum switching voltage | 250 V AC 125 V DC |
| Minimum switching voltage | 1 V |
| Limiting continuous current | 5 A |
| Maximum inrush current | 12 A (15 ms) |
| Min. switching current | 1 mA |
| Interrupting rating (ohmic load) max. | see diagram 1250 VA (for 250 V AC) |

Environmental and real-life conditions

REL-IRG 24 - Single relay

2960261

<https://www.phoenixcontact.com/us/products/2960261>



Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -55 °C ... 70 °C |
| Ambient temperature (storage/transport) | -55 °C ... 70 °C |

Standards and regulations

| | |
|-----------------------|--------------|
| Standards/regulations | IEC 60664 |
| | IEC 60664A |
| | DIN VDE 0110 |

REL-IRG 24 - Single relay



2960261

<https://www.phoenixcontact.com/us/products/2960261>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2960261>



EAC

Approval ID: TR_TS_D_00573_c



EAC

Approval ID: RU*C-DE.*08.B.00010

REL-IRG 24 - Single relay

2960261

<https://www.phoenixcontact.com/us/products/2960261>



Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27371601 |
| ECLASS-12.0 | 27371601 |
| ECLASS-13.0 | 27371601 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC001437 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39122300 |
|-------------|----------|

REL-IRG 24 - Single relay



2960261
<https://www.phoenixcontact.com/us/products/2960261>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com