

# SD FLASH 512MB - Program / configuration memory



2988146

<https://www.phoenixcontact.com/us/products/2988146>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Program and configuration memory, plug-in, 512 Mbyte.



## Your advantages

- For storing application programs and other files in the file system of the PLC
- Program and configuration memory, plug-in
- Easy reproduction of configurations
- Easy device replacement

## Commercial data

Item number	2988146
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR10
Product key	DRAAZA
Catalog page	Page 22 (C-6-2019)
GTIN	4046356342674
Weight per piece (including packing)	9.8 g
Weight per piece (excluding packing)	8.5 g
Customs tariff number	85235110
Country of origin	TW

# SD FLASH 512MB - Program / configuration memory



2988146

<https://www.phoenixcontact.com/us/products/2988146>

## Technical data

### Product properties

Product type	Storage medium
Mounting position	vertical
Application	Program/configuration memory

### Electrical properties

Maximum power dissipation for nominal condition	0.165 W
---	---------

#### Supply

Supply voltage	3.3 V DC
Supply voltage range	2.7 V DC ... 3.6 V DC
Typical current consumption	typ. 50 mA

### Material specifications

Housing material	Plastic
------------------	---------

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

### Mounting

Mounting position	vertical
-------------------	----------

# SD FLASH 512MB - Program / configuration memory



2988146

<https://www.phoenixcontact.com/us/products/2988146>

## Classifications

### ECLASS

ECLASS-11.0	27242212
ECLASS-12.0	27242212
ECLASS-13.0	27242212

### ETIM

ETIM 8.0	EC000192
----------	----------

### UNSPSC

UNSPSC 21.0	32101600
-------------	----------

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

# SD FLASH 512MB - Program / configuration memory



2988146

<https://www.phoenixcontact.com/us/products/2988146>

## Accessories

### ILC 131 ETH - Controller

2700973

<https://www.phoenixcontact.com/us/products/2700973>



The Inline controller offers the option of communicating via PROFINET and Modbus/TCP. Programming is carried out using PC Worx Express or PC Worx (IEC 61131-3).

---

### ILC 131 ETH/XC - Controller

2701034

<https://www.phoenixcontact.com/us/products/2701034>



Inline controller for use under harsh ambient conditions, with Ethernet interface for coupling to other controllers and systems, with programming options according to IEC 61131-3, complete with connector and labeling field.

# SD FLASH 512MB - Program / configuration memory



2988146

<https://www.phoenixcontact.com/us/products/2988146>

## ILC 151 ETH - Controller

2700974

<https://www.phoenixcontact.com/us/products/2700974>



The Inline controller offers the option of communicating via PROFINET and Modbus/TCP. Programming is carried out using PC Worx Express or PC Worx (IEC 61131-3).

---

## ILC 151 ETH/XC - Controller

2701141

<https://www.phoenixcontact.com/us/products/2701141>



Inline controller for use under harsh ambient conditions, with Ethernet interface for coupling to other controllers and systems, with programming options according to IEC 61131-3, complete with connector and labeling field.

# SD FLASH 512MB - Program / configuration memory



2988146

<https://www.phoenixcontact.com/us/products/2988146>

## ILC 171 ETH 2TX - Controller

2700975

<https://www.phoenixcontact.com/us/products/2700975>



The Inline controller offers the option of communicating via PROFINET and Modbus/TCP. Programming is carried out using PC Worx Express or PC Worx (IEC 61131-3).

---

## ILC 191 ETH 2TX - Controller

2700976

<https://www.phoenixcontact.com/us/products/2700976>



The Inline controller offers the option of communicating via PROFINET and Modbus/TCP. Programming is carried out using PC Worx Express or PC Worx (IEC 61131-3).

# SD FLASH 512MB - Program / configuration memory



2988146

<https://www.phoenixcontact.com/us/products/2988146>

## ILC 191 ME/AN - Controller

2700074

<https://www.phoenixcontact.com/us/products/2700074>



Inline controller with integrated pulse/direction/PWM interface, RS-485/RS-422, analog inputs (0 ... 10 V), and analog outputs (0 ... 10 V), with programming options according to IEC 61131-3

---

## ILC 191 ME/INC - Controller

2700075

<https://www.phoenixcontact.com/us/products/2700075>



Inline controller with integrated pulse/direction/PWM interface, RS-485/RS-422, fast counters, and incremental encoder inputs, with programming options according to IEC 61131-3



# SD FLASH 512MB - Program / configuration memory



2988146

<https://www.phoenixcontact.com/us/products/2988146>

## AXC 1050 - Controller

2700988

<https://www.phoenixcontact.com/us/products/2700988>



Axio control for direct open-loop control of Axioline I/Os. With 2 Ethernet interfaces and programming capabilities according to IEC 61131-3. Complete with connector connector and labeling field.

---

## AXC 1050 XC - Controller

2701295

<https://www.phoenixcontact.com/us/products/2701295>



Axiocontrol for the direct control of Axioline I/Os. With 2 Ethernet interfaces, extended temperature range, and programming options according to IEC 61131-3. Complete with connector connector and marking field.

---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)