

BXT-4XP-SEC-T3-120+1X2-24 - Surge protection device



2908684

<https://www.phoenixcontact.com/us/products/2908684>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Wall-mounted NEMA 4/4X (IP66/67) polycarbonate enclosure with surge protection for 120 V AC/DC power and one 24 V DC loop with 28 V DC MCOV

Your advantages

- Eligible for limited lifetime warranty (in some U.S. markets)
- Customizable: expand base unit with SPDs to suit your application
- Polycarbonate and 316L stainless steel enclosures available
- UL 1449 Listed SPD

Commercial data

Item number	2908684
Packing unit	1 pc
Sales key	CL20
Product key	CL1481
GTIN	4055626321486
Weight per piece (including packing)	222.222 g
Weight per piece (excluding packing)	222.222 g
Country of origin	DE

BXT-4XP-SEC-T3-120+1X2-24 - Surge protection device



2908684

<https://www.phoenixcontact.com/us/products/2908684>

Set consists of

PLT-SEC-T3-120-FM-UT - Type 3 surge protection device

2907918

<https://www.phoenixcontact.com/us/products/2907918>



Type 2/3 surge protection, consisting of protective plug and base element, with integrated status indicator and remote signaling for single-phase power supply networks. Nominal voltage: 120 V AC/DC

PT 1X2-24DC-ST - Surge protection plug

2856032

<https://www.phoenixcontact.com/us/products/2856032>



PT protective connector with protective circuit for a 2-wire floating signal circuit. HART-compatible.

BXT-4XP-SEC-T3-120+1X2-24 - Surge protection device




2908684

<https://www.phoenixcontact.com/us/products/2908684>

PT 1X2+F-BE - Surge protection base-element

2856126

<https://www.phoenixcontact.com/us/products/2856126>



Base element for protective plug PT with protective circuit for a 2-core floating signal circuit. Integrated gas arrester as coarse protection between GND and PE. Mounting on NS 35/7.5 und NS 35/15, housing width: 17.5 mm.

BXT-4XP-SEC-T3-120+1X2-24 - Surge protection device



2908684

<https://www.phoenixcontact.com/us/products/2908684>

Technical data

Product properties

Type	DIN rail module, two-section, divisible
Product type	Device protection
Surge protection fault message	optical
EN type	T2 / T3
Number of ports	One

Electrical properties

Nominal voltage U_N	120 V AC (Power)
	24 V DC (Signal)

Indicator/remote signaling

Connection name	Remote fault indicator contact
Switching function	Changeover contact

Connection data

Screw thread	M3
Tightening torque, min	0.5 Nm
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section, rigid min.	0.2 mm ²
Conductor cross section, rigid max.	4 mm ²
Connection method	Screw connection
Screw thread	M3

Dimensions

Dimensional drawing	
Width	130 mm
Height	180 mm
Depth	120 mm

Material specifications

Housing material	PC (polycarbonate)
------------------	--------------------

Protective circuit

Power supplies

Direction of action	L/N-PE & Signal Line-Shield-Earth Ground
---------------------	--

BXT-4XP-SEC-T3-120+1X2-24 - Surge protection device



2908684

<https://www.phoenixcontact.com/us/products/2908684>

Nominal voltage U_N	120 V AC (TN-S)
	120 V AC (TT)

Information technology

Max. operating voltage U_{max}	150 V AC (Power)
	28 V DC (Signal)
Max. discharge current I_{max} (8/20) μ s	10 kA (Power)
Max. discharge current I_{max} (8/20) μ s maximum (line-line)	10 kA (Signal)
Max. discharge current I_{max} (8/20) μ s maximum (line-earth)	10 kA (Signal)
Resistance per path	2.2 Ω (Signal)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66 / NEMA 4X
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	\leq 2000 mm
Permissible humidity (operation)	5 % ... 95 %

Approvals

UL specifications

Maximum continuous operating voltage MCOV	150 V AC/DC
Short-circuit current rating (SCCR)	10 kA
Voltage protection rating VPR (L-N)	700 V
Voltage protection rating VPR (L-G)	1000 V
Voltage protection rating VPR (N-G)	900 V
Voltage protection rating VPR (DC+) - (DC-)	700 V
Voltage protection rating VPR (DC+) - G	1000 V
Voltage protection rating VPR (DC-) - G	900 V
UL type	type 2
Nominal discharge current I_n	5 kA
Maximum Circuit Breaker	25 A
Maximum Surge Current per Phase	20 A

Mounting

Mounting type	Wall mounting
---------------	---------------


BXT-4XP-SEC-T3-120+1X2-24 - Surge protection device



2908684

<https://www.phoenixcontact.com/us/products/2908684>

Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2908684>



UL Listed

Approval ID: FILE E 330181



cUL Listed

Approval ID: FILE E 330181

cULus Listed

BXT-4XP-SEC-T3-120+1X2-24 - Surge protection device



2908684
<https://www.phoenixcontact.com/us/products/2908684>

Classifications

ECLASS

ECLASS-11.0	27130810
ECLASS-13.0	27171602

BXT-4XP-SEC-T3-120+1X2-24 - Surge protection device



2908684

<https://www.phoenixcontact.com/us/products/2908684>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
	4-Nonylphenol, branched and linear
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com