

P-DI - Isolating plugs

3036783

<https://www.phoenixcontact.com/us/products/3036783>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Isolating plugs, length: 10.8 mm, width: 3.5 mm, height: 10.8 mm, color: orange

Your advantages

- Can be used in all ...-TG disconnect terminal blocks from the CLIPLINE complete system
- The P-DI isolating plug can be easily removed to release the connection and then "parked" back to front in the disconnect zone

Commercial data

Item number	3036783
Packing unit	1 pc
Minimum order quantity	50 pc
Sales key	BE29
Product key	BE2ZWX
Catalog page	Page 415 (C-1-2019)
GTIN	4017918901998
Weight per piece (including packing)	0.701 g
Weight per piece (excluding packing)	0.617 g
Customs tariff number	85366990
Country of origin	DE

P-DI - Isolating plugs

3036783

<https://www.phoenixcontact.com/us/products/3036783>



Technical data

Product properties

Product type	Knife
--------------	-------

Dimensions

Width	3.5 mm
Height	10.8 mm
Depth	23.1 mm
Length	10.8 mm

Material specifications

Color	orange
Flammability rating according to UL 94	V2
Insulating material	PA
Static insulating material application in cold	-40 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

P-DI - Isolating plugs


3036783


<https://www.phoenixcontact.com/us/products/3036783>




Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3036783>

	CSA Approval ID: 13631			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	-	15 A	-	-

	IECEE CB Scheme Approval ID: DE1-62955			
---	--	--	--	--

	EAC Approval ID: RU C-DE.BL08.B.00511			
---	---	--	--	--

	BV Approval ID: 25278/C1 BV			
---	---------------------------------------	--	--	--

	VDE Zeichengenehmigung Approval ID: 40037480			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	-	-	-	0.2 - 4

P-DI - Isolating plugs

3036783

<https://www.phoenixcontact.com/us/products/3036783>



Classifications

ECLASS

ECLASS-11.0	27141192
ECLASS-12.0	27141192
ECLASS-13.0	27141192

ETIM

ETIM 8.0	EC002848
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

P-DI - Isolating plugs



3036783
<https://www.phoenixcontact.com/us/products/3036783>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com