

# WP-EC TPE HF 42,5 BK - Transition sleeve from hose to cable



3240980

<https://www.phoenixcontact.com/us/products/3240980>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Transition sleeve from hose to cable, material: TPE, color: black, flammability rating in acc. with UL 94: HB

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3240980             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 25 pc               |
| Sales key                            | BF68                |
| Product key                          | BF7DSA              |
| Catalog page                         | Page 585 (C-3-2019) |
| GTIN                                 | 4046356710985       |
| Weight per piece (including packing) | 14.252 g            |
| Weight per piece (excluding packing) | 14.252 g            |
| Customs tariff number                | 39174000            |
| Country of origin                    | DE                  |

# WP-EC TPE HF 42,5 BK - Transition sleeve from hose to cable



3240980

<https://www.phoenixcontact.com/us/products/3240980>

## Technical data

### Product properties

|              |                |
|--------------|----------------|
| Product type | Protective cap |
|--------------|----------------|

### Dimensions

|          |         |
|----------|---------|
| Length   | 46 mm   |
| Diameter | 42.5 mm |

### Material specifications

|  |              |
|--|--------------|
| Material                               | TPE          |
| Flammability rating according to UL 94 | HB           |
| Components                             | halogen-free |

### Environmental and real-life conditions

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C |
| Short-term temperature          | 150 °C            |

# WP-EC TPE HF 42,5 BK - Transition sleeve from hose to cable



3240980

<https://www.phoenixcontact.com/us/products/3240980>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3240980>



UL Recognized

# WP-EC TPE HF 42,5 BK - Transition sleeve from hose to cable



3240980

<https://www.phoenixcontact.com/us/products/3240980>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27430316 |
| ECLASS-13.0 | 27430316 |
| ECLASS-12.0 | 27430316 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC000519 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# WP-EC TPE HF 42,5 BK - Transition sleeve from hose to cable



3240980

<https://www.phoenixcontact.com/us/products/3240980>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)