

NMUA TYPE B NON-METALLIC HOSE UL LISTED AND CSA APPROVED

LFNC SEALTITE® NMUA (TYPE B)
NON-METALLIC FLEXIBLE CONDUIT



DESCRIPTION

- Non-metallic Type B liquid tight conduit
- Designed for standard commercial and industrial applications
- Approved in US (per NEC) for direct burial applications
- Also available by special order in other colors (consult the factory)
- Uses special non-metallic connectors for easy installation
- Can also be used with a liquid tight connector
- Additional Put-ups available

COMMON NEC Articles

- 300.22 (D) Information Technology Equipment
- Suitable for hazardous locations per NEC Articles
 - 501.10 (B) (2) Class I Div. 2
 - 502.10 (A) (2) and (B) (2) Class II Div. 1 & 2
 - 503.10 (A) (3) and (B) Class III Div. 1 & 2
- 356 Liquid tight Flexible Nonmetal Conduit (LFNC-B)
- 645.5 (E) (2) Under raised floors

SPECIFICATIONS

- Smooth Inner and Outer PVC Walls with a Co-Extruded Reinforcing PVC Coil
- Color: Gray
- Temp. range: -17°F to +176°F (-27°C to +80°C)
- UV (sunlight) resistant
- Oil resistant
- UL 1660 Approved #E211327
- CSA Approved #20817

APPLICATIONS

- HVAC industry
- Commercial and industrial applications requiring UL and CSA approvals

See: www.ul.com www.csa-international.org
www.nfpa.org www.naed.org
www.nema.org www.anacondasealtite.com



Smooth Inner and Outer PVC Walls with a Co-Extruded Reinforcing PVC Coil 3/8" - 2"



Trade Size (mm)	Item ID	Std. Pkg. (feet)	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)	Packages per Pallet
			Min	Max	Min	Max			
3/8" (12)	39702	100	0.484	0.504	0.690	0.710	2.0	11	60
	39708	1000							3
1/2" (16)	39712	100	0.622	0.640	0.820	0.840	3.3	15	48
	39713	1000							3
3/4" (21)	39722	100	0.820	0.840	1.030	1.050	4.5	20	36
	39724	700							3
1" (27)	39731	100	1.041	1.066	1.290	1.315	6.5	27	28
	39734	500							3
1-1/4" (35)	39741	50	1.380	1.410	1.630	1.660	8.0	36	28
	39742	100							12
1-1/2" (41)	39753	50	1.575	1.600	1.865	1.900	9.0	45	24
	39752	100							12
2" (53)	39761	50	2.020	2.045	2.340	2.375	11.1	67	12
	39768	100							3

FITTINGS FINDER



PAGE 54

NON-METALLIC SEALTITE®

N
M
U
A