

Product data sheet

Specifications



Sealed pressure balance valves IP68 ØM12 F120 liters/hour when 0,07 bar

NSYCAG12LPH2

Main

Range	ClimaSys
Product	ClimaSys CA
Range compatibility	Thalassa (Thalassa PLS) Thalassa (Thalassa PLM) Thalassa (Thalassa TBS) Thalassa (Thalassa TBP)
Product or component type	Pressure release valve
Accessory / separate part category	Thermal management accessory
Environmental characteristic	Water resistant
Fixing mode	Screwed
Device composition	1 valve
Quantity per set	Set of 10

Complementary

Material	Membrane: acrylic co-polymer PA6
Diameter	10.2 mm
Height	30 mm
Width	140 mm
Flame retardance	V2
Operating temperature	-40...150 °C
Permeability	120 l/h
Pressure difference	< 0.1 bar

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	14.0 cm
Package 1 Length	12.0 cm
Package 1 Weight	4.0 g

Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	3.0 cm
Package 2 Width	14.0 cm
Package 2 Length	12.0 cm
Package 2 Weight	40.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)