

Product data sheet

Specifications



Multi-fixing LED lamp with socket USA - 120 V AC - 10W

NSYLAMLDU

Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 lamp 1 fixing elements
Power factor	0.9

Complementary

Outlet standard	United States
Rated lamp wattage	10 W
[Ue] rated operational voltage	120 V AC 50/60 Hz
Bulb base	Integral LED
Bulb type	LED
Control type	Built-it switch
Luminous flux	950 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 3 m not supplied Cable quick connector 1 m not supplied
Mounting support	Bracket DIN rail Metal parts
Fixing mode	Clip-in Magnetic fixing Screws
Range compatibility	Spacial Thalassa
Material	PC (UL94 V-0)
Length	372 mm
Height	63 mm
Width	40 mm

Colour	Black (RAL 9005)
--------	------------------

Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical insulation class	Class I
Electromagnetic compatibility	EMC immunity conforming to EN 55015
Standards	UL 1598 IEC 60598 EN 55015 CSA C22.2 No 14-10 UL 94 UL 8750 UL 508 A
Ambient air temperature for operation	-16...65 °C
Ambient air temperature for storage	-10...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	8.2 cm
Package 1 Length	40.0 cm
Package 1 Weight	845.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)