


ZB 7,62/WH-100:UNBEDRUCKT - Zack marker strip



5060922

<https://www.phoenixcontact.com/us/products/5060922>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 7.62 mm, lettering field size: 10.5 x 7.5 mm, Number of individual labels: 1000

Your advantages

- Labeling service: Phoenix Contact can custom-label all zack marker strip markers according to your requirements
- The ZB zack marker strip system is a marking solution for modular terminal blocks and electronics modules with tall marker grooves

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 5060922 |
| Packing unit | 1 pc |
| Minimum order quantity | 100 pc |
| Sales key | BG05 |
| Product key | BG2112 |
| Catalog page | Page 119 (C-3-2019) |
| GTIN | 4017918096151 |
| Weight per piece (including packing) | 1.662 g |
| Weight per piece (excluding packing) | 1.532 g |
| Customs tariff number | 39269097 |
| Country of origin | DE |

Technical data

Notes

| | |
|---------|-------------------------|
| General | Can be labeled with CMS |
|---------|-------------------------|

Product properties

| | |
|--------------|------------------|
| Product type | Terminal marking |
| Pitch | 7.62 mm |
| Type | high |

Marking

| | |
|-------------------------------------|------|
| Number of individual labels | 1000 |
| Number of individual labels per row | 10 |
| Number of marker strips | 100 |

Dimensions

| | |
|-------|---------|
| Width | 7.5 mm |
| Pitch | 7.62 mm |

Material specifications

| | |
|--|--------------------------------|
| Color | white |
| Material | PA |
| Flammability rating according to UL 94 | V2 |
| Base element material | PA |
| Components | free from silicone and halogen |

Environmental and real-life conditions

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
|---------------|--------------------------------|

Ambient conditions

| | |
|---|-------------------|
| Ambient temperature (operation) | -40 °C ... 100 °C |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |

Standards and regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Mounting

| | |
|---------------|---------|
| Mounting type | snapped |
|---------------|---------|

5060922

<https://www.phoenixcontact.com/us/products/5060922>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27281101 |
| ECLASS-12.0 | 27281101 |
| ECLASS-13.0 | 27281101 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000761 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com