

EM-DUO 120/20/V/H - Socket



5604776

<https://www.phoenixcontact.com/us/products/5604776>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Rail-mounted dual socket for vertical or horizontal mounting on 35 mm DIN rail per EN 60715.
Housing color: ivory. Receptacle style: USA. Connection type: screw.

Commercial data

Item number	5604776
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BE76
Product key	BE7613
GTIN	4046356684507
Weight per piece (including packing)	33.33 g
Weight per piece (excluding packing)	33.33 g
Customs tariff number	85366990
Country of origin	US

Technical data

Notes

Trade restriction

CE note	The products are offered exclusively for export outside the EU and the European Economic Area.
---------	--

Product properties

Product type	Socket
For country-specific use in	USA
	Canada
	Japan
	Mexico
	Saudi Arabia
	Taiwan
	Venezuela

Electrical properties

Nominal voltage U_N	125 V AC
Nominal current I_N	20 A

Material specifications

Color	ivory
Insulating material	PVC 94 V0
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 60 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %

EM-DUO 120/20/V/H - Socket



5604776

<https://www.phoenixcontact.com/us/products/5604776>

Standards and regulations

Standards

Standards/regulations	UL 508
	CSA 22.2

Mounting

Connection method	Screw connection
-------------------	------------------

EM-DUO 120/20/V/H - Socket



5604776

<https://www.phoenixcontact.com/us/products/5604776>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/5604776>



UL Listed

Approval ID: FILE E 238705

	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	125 V	20 A	-	30 - 10



cUL Listed

Approval ID: FILE E 238705

	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	125 V	20 A	30 - 10	-

cULus Listed

EM-DUO 120/20/V/H - Socket

5604776

<https://www.phoenixcontact.com/us/products/5604776>



Classifications

ECLASS

ECLASS-11.0	27142305
ECLASS-12.0	27142305
ECLASS-13.0	27142305

ETIM

ETIM 8.0	EC001663
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

EM-DUO 120/20/V/H - Socket



5604776

<https://www.phoenixcontact.com/us/products/5604776>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com