

# PI/NI-2D/24 - Signal conditioner



5607118

<https://www.phoenixcontact.com/us/products/5607118>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



## Product description

The PI/NI-2D/24 barrier works with two-wire transmitters to prevent short circuits from causing explosions in Class I, Division 2 and Class I, Zone 2 environments.

## Commercial data

Item number	5607118
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DN11
Product key	DNC1Z1
GTIN	4046356684767
Weight per piece (including packing)	105.4 g
Weight per piece (excluding packing)	69 g
Customs tariff number	85369010
Country of origin	US

## Technical data

### Notes

#### Trade restriction

CE note	The products are offered exclusively for export outside the EU and the European Economic Area.
---------	--

### Product properties

Product type	Signal conditioner
No. of channels	2

### Electrical properties

No. of channels	2
-----------------	---

### Input data

#### Signal

Description of the input	Digital input
Number of inputs	2
Input signal	Voltage
Voltage input signal	24 V DC ... 24 V DC $\pm 20$ %

### Output data

#### Signal

Number of outputs	2
Voltage output signal	24 V DC ... 24 V DC $\pm 20$ %

### Connection data

Connection method	Screw
Conductor cross section AWG	30 ... 12
Tightening torque	5 lb <sub>F</sub> -in. ... 7 lb <sub>F</sub> -in.

### Ex data

#### Safety data

Max. output voltage $U_o$	35 V DC
Max. output current $I_o$	75 mA
Max. output power $P_o$	2.6 W
Max. external inductivity $L_o$ / Max. external capacitance $C_o$	/ 102 $\mu$ F 8.58 mH

### Dimensions

Width	17 mm
Height	94 mm

# PI/NI-2D/24 - Signal conditioner



5607118

<https://www.phoenixcontact.com/us/products/5607118>

Depth	70 mm
-------	-------

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 70 °C

## Approvals

### Ex data

UL, USA / Canada	Class I, Zone 2, AEx nA [nC] IIC T4
	Class I, Zone 2, Ex nA [nL] IIC T4 X
	Class I, Div. 2, Groups A, B, C, D T4

# PI/NI-2D/24 - Signal conditioner





5607118


<https://www.phoenixcontact.com/us/products/5607118>


## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/5607118>

 <b>UL Listed</b> Approval ID: FILE E 238705				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
Output	35 V	0.075 A	-	30 - 10

 <b>cUL Listed</b> Approval ID: FILE E 238705				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
Output	35 V	0.075 A	30 - 10	-

 <b>cUL Listed</b> Approval ID: FILE E 199827				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
Output	35 V	0.075 A	30 - 12	-

 <b>UL Listed</b> Approval ID: FILE E 199827				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
Output	35 V	0.075 A	30 - 12	-

<b>cULus Listed</b>				
---------------------	--	--	--	--

<b>cULus Listed</b>				
---------------------	--	--	--	--

# PI/NI-2D/24 - Signal conditioner



5607118

<https://www.phoenixcontact.com/us/products/5607118>

## Classifications

### ECLASS

ECLASS-11.0	27210120
ECLASS-12.0	27210120
ECLASS-13.0	27210120

### ETIM

ETIM 8.0	EC002653
----------	----------

### UNSPSC

UNSPSC 21.0	39121000
-------------	----------

# PI/NI-2D/24 - Signal conditioner



5607118

<https://www.phoenixcontact.com/us/products/5607118>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)