



Material : NYLON 66,

Fire-proof level: 94V-2

Application: For PC board, iron plate parts are fixed, instead of screws, saving time and no tools.

Unit: mm

Model Item No.	Diameter	Applicable plate thickness	A	B	C	D	E	Pulling force	Packing
R2024	2.1	0.6~1.2	4.2	1.2	2.4	2.0	3.8	3Kg	1000PCS
R2032		1.3~3.0			3.2				
R2040		2.1~2.8			4.0				
R2048		2.9~3.6			4.8				
R2056		3.7~4.4			5.6				
R2064		4.5~5.2			6.4				
R2632	2.7	1.0~2.0	5.0	1.4	3.2	2.6	4.6	5Kg	
R2642		2.1~3.0			4.2				
R2648		2.7~3.6			4.8				
R2655		3.4~4.3			5.5				
R2664		4.3~5.2			6.4				
R2672		5.1~6.0			7.2				
R3035	3.1	1.0~2.0	6.4	1.6	3.5	3.0	5.1	8Kg	
R3045		2.0~3.0			4.5				
R3055		3.0~4.0			5.5				
R3065		4.0~5.0			6.5				
R3075		5.0~6.0			7.5				
R3080		5.5~6.5			8.0				
R3090		6.5~7.5			9.0				
R3100		7.5~8.5			10.0				
R3230		20.5~21.5			23.0				
R3535	3.6	1.2~2.1	6.4	1.6	3.5	3.5	5.1	12Kg	
R3545		2.2~3.1			4.5				
R3550		2.7~3.6			5.0				
R3555		3.2~4.1			5.5				
R3560		3.7~4.6			6.0				
R3570		4.7~5.5			7.0				
R3580		5.7~6.6			8.0				
R3588		7.3~8.3			8.5				
R4050	4.1	2.5~3.5	8.0	1.8	5.0	4.0	7.1	20Kg	
R4060		3.5~4.5			6.0				
R4070		4.5~5.5			7.0				
R4080		5.5~6.5			8.0				
R4090		6.5~7.5			9.0				
R4100		7.5~8.5			10.0				
R4120		9.0~10.5			12.0				14.0
R5045	5.1	1.5~2.5	9.0	2.2	4.5	5.0	6.5	25Kg	
R5055		2.5~3.5			5.5				
R5065		3.5~4.5			6.5				
R5075		4.5~5.5			7.5				
R5085		5.5~6.5			8.5				
R5095		6.5~7.5			9.5				
R5105		7.5~8.5			10.5				
R6060	6.1	2.5~4.0	12.0	2.5	6.0	6.0	9.0	30Kg	
R6080		4.0~5.5		3.0					8.0