High Quality Power Cord UL Certificated

RoHS Compliant



438.4±76.2 (96"±3")—

(Wire Cross-Section)



(NEMA 5-15P) Dimensions of Plug Face)

Component

4.75 GEM 98475ABS-1

(#14-#18) Earth Pins Terminal 6.3×1.5 (#14AWG) GEM

98675BBS-1 (Solid Blades)

301-1 (5-15P Inner Body)

Plug Component

(NEMA 5-15P)

PVC Insulation Thickness 0.78(>0.70mm)
Green Overall Diameter 3.05±0.10mm
Copper Conductor 65/0.160±0.003mm
Diameter 1.50mm (Approx.)
White Black PVC Jacket Thickness 0.78mm(>0.70mm)
Overall Diameter 8.5±0.2mm
SJT 16AWGx3C

Dimension				
Strip	ROJ	Colour		
6 +1/-0	22 ±2	Black (L)		
6 +1/-0	22 ±2	White (N)		
6 +1/-0	22 ±2	Green (E)		
		Г		

Wire Styles SJT 16AWGx3C 60°C Black Length: 2,438.4mm ±76.2mm 96" ±3"

Dimensions			
ROJ	Strip	Colour	
51 ±6	16 ±3	Black (L)	
51 ±6	16 ±3	White (N)	
51 ±6	16 ±3	Green (E)	

Dimensions: Millimetres

Note:

Colour

35P (Black)

Nickel-Plated

Nickel-Plated

Black

1. Hi-Pot Test : 1,500V/1Sec; <0.5mA

2. Insulation Resistance Test : DC 500/min>100mΩ

3. Continuity & Polarization Test: No short circuit, break circuit, displacement.

4. Each end terminal shall be capable of withstanding a pull of 25lbs for 1 minutes without loosening.

Qty

1

2

1

- 5. Strain relief shall be capable of withstanding a pull of 35lbs for 1 minutes without loosening.
- 6. All material according to Non-toxic standard.

Part Number Table

Description	Part Number
5-15P, SJT, 16×3, 13A 125V	P09601US-SJT

Important Notice: This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from hegligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.

Page <1> 10/01/23 V1.0