High Quality Power Cord

UL Certificated

ME-301 (NEMA 5-15P) (Dimensions of Plug Face)

r lag compensit				
Colour	Component			
35P (Black)	(NEMA 5-15P)			
Nickel-Plated	4.75 GEM 98475ABS-1 (#14-#18) Earth Pins Terminal			
Nickel-Plated	6.3×1.5 (#14AWG) GEM 98675BBS-1 (Solid Blades)	2		
Black	301-1 (5-15P Inner Body)	1		

Note:

Dimensions : Millimetres

- 1. Hi-Pot Test : 1,500V/1Sec; <0.5mA
- 2. Insulation Resistance Test : DC 500/min>100mΩ
- 3. Continuity & Polarization Test : No short circuit, break circuit, displacement.
- 4. Each end terminal shall be capable of withstanding a pull of 25lbs for 1 minutes without loosening.
- 5. Strain relief shall be capable of withstanding a pull of 35lbs for 1 minutes without loosening.
- 6. All material according to Non-toxic standard.

Part Number Table

Description	Part Number
5-15P, SVT, CEE, 18×3, 10A 125V	P11801US-SVT

Important Notice : This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.

10/01/23 V1.0



Filler Strip

PVC Insulation Thickness 0.46(>0.41mm) Overall Diameter 2.10±0.08mm Vell Copper Conductor 41/0.160±0.003mm Diameter 1.18mm (Approx.) Cotton Parer ¹/₄ Lap Warp PVC Jacket Thickness 0.84mm(>0.76mm)

SVT 18AWGx3C (Wire Cross-Section)

Dimension				
Strip	ROJ	Colour		
6 +1/-0	22 ±2	Brown (L)		
6 +1/-0	22 ±2	Blue (N)		
6 +1/-0	22 ±2	Green-Yellow (E)		

Wire Styles

SVT 18AWGx3C 60°C Black Length : 2,997.2mm ±76.2mm 118" ±3"

Dimensions					
ROJ	Strip	Colour			
51 ±6	16 ±3	Brown (L)			
51 ±6	16 ±3	Blue (N)			
51 ±6	16 ±3	Green-Yellow (E)			



RoHS

Compliant