



High Quality Power Cord

UL Certificated


**RoHS
Compliant**



(NEMA 5-15P, Hospital Grade)
(Dimensions of Plug Face)



SJT 16AWGx3C
(Wire Cross-Section)



(IEC 60320, C13, 13A 125V~)
(Dimensions of Connector Face)

Dimensions : Millimetres

Plug Component		
Colour	Component	Qty
35P	(Nema 5-15P, Hospital Grade)	1
Nickel-plated	4.75 "U" GEM 98478BBL-1 U-type Earth Pins Terminal	1
Nickel-plated	6.3×15 Solid Blades/ GEM98693ABL-1	2
	18AWG, ID 6mm, (10-13mm) Metal Washer	3

Dimension		
Strip	ROJ	Colour
6 +1/-0	70 ±2	Black (L)
6 +1/-0	70 ±2	White (N)
6 +1/-0	80 ±2	Green (E)

Wire Styles

SJT16AWGx3C

60°C

Length : 1828.8mm

±18.3mm

72" ±0.72"

Connector Component		
Instruction	Qty.	Colour
(IEC 60320, C13, 13A, 125V)	1	35p (Black)
2.0 × 4.0 GEM 98740BS-0 (#16-18) Receptacle Terminal	3	Brass-Natural
GA005-5 (2.0 × 4.0 Serial Housing)	1	Off-White

Dimensions		
ROJ	Strip	Colour
16±1	5 +1/-0	Black (L)
16±1	5 +1/-0	White (N)
16±1	5 +1/-0	Green (E)

Dimensions : Millimetres

High Quality Power Cord

UL Certificated

Note:

1. Hi-Pot Test : 1,500V/1Sec; <0.5mA
2. Insulation Resistance Test : DC 500/min>100mΩ
3. Continuity & Polarization Test : No short circuit, break circuit, displacement.
4. Each end terminal shall be capable of withstanding a pull of 25lbs for 1 minutes without loosening.
5. Strain relief shall be capable of withstanding a pull of 35lbs for 1 minutes without loosening.
6. All material according to Non-toxic standard.



Part Number Table

Description	Part Number
NEMA 5-15P HG to IEC 60320, SJT 16×3, C13, 13A 125V	PC06002US-HG-SJT

Important Notice : This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.