
Mains Power Cord Schuko Plug to IEC60320-C13







Dimensions : Millimetres






PVC Insulation Thickness 0.60(>0.44mm) Overall Diameter 2.50±0.08mm


-2500±50.8 (98.4"±2")-

Resistance (@20°C Max.) : 18.2Ω/km PVC Jacket Thickness 0.08m(>0.58m) Overall Diameter 7.1±0.20m

Copper Conductor 32/0.20±0.007nm



(T/0.08cm) (Insert Into a Clear Plastic Bag)



(CEE7 st. sh VII, Schuko, 16A 250V~) H05WV-F 1.0m*x3G (Dimensions of Plug Face) (Wire Cross-Section)

Plug Component			Plug Component (Dimension)			
Colour	Component	Qty	Strip	ROJ	Colour	
45P (Black)	(CEE7 st. sh VII, Schuko, 16A 250V)	1	6 +1/-0	30 ±2	Brown (L)	
Black	GEM 98651A-VDE/0 (Ø4.76 VDE Plug Insert)	1	6 +1/-0	30 ±2	Blue (N)	
			6 +1/-0	30 ±2	Green-Yellow (E)	

Connector Component			Connector Component (Dimensions)		
(Instruction)	Qty.	Colour	ROJ	Strip	Colour
(IEC 60320, C13, 10A 250V)	1	45P (Black)	16±1	5 +1/-0	Brown (L)
2.0 × 4.0 GEM 98740BS-0 (#16-18) (Receptacle Terminal)	3	(Brass-Natural)	16±1	5 +1/-0	Blue (N)
GA005-5 (2.0 × 4.0 Serial Housing)	1	(Off-White)	16±1	5 +1/-0	Green-Yellow (E)

Mains Power Cord Schuko Plug to IEC60320-C13



Note

- 1, Hi-Pot Test : 1500V/1Sec; <0.5mA.
- 2, Continuity & Polarization Test : No short circuit, break circuit displacement.
- 3, Conductor Secureness Test :≥18AWG 20lb; ≤18AWG 8lb; 1min.
- 4, Each end terminal shall be capable of withstanding a pull of #1820lb, #1630lb, #1450lb, #1270lb, #1080lb for 1min. without loosening.
- 5, Strain relief shall be Capable of withstanding a pull of ≤18AWG 20lb;≥18AWG 301b;Imin. without loosening.
- 6, All material according to Non-toxic standard.



Part Number Table

Description	Part Number
Mains Power Cord, Schuko Plug to IEC60320-C13, 16A, 250V, Black, 8ft	PC11801US-H05VV

Important Notice : This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage arising) is excluded. This will not operate to limit or restrict the Group vas aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.