


High Quality Power Cord

UL Certificated

**RoHS
Compliant**



Dimensions : Millimetres

| Plug Component | | |
|----------------|--------------------------|-----|
| Colour | Component | Qty |
| 35P (Black) | (Nema 6-15P) | 1 |
| Nickel-plated | 4.75 Earth Pins Terminal | 1 |
| Nickel-plated | 6.3×1.5 (Solid Blades) | 2 |
| Black | GA39-01 Inner Body | 1 |

| Dimension | | |
|-----------|-------|------------------|
| Strip | ROJ | Colour |
| 6 +1/-0 | 22 ±2 | Brown (L) |
| 6 +1/-0 | 22 ±2 | Blue (N) |
| 6 +1/-0 | 22 ±2 | Green-Yellow (E) |

Wire Styles

SJT 18AWGx3C
(CEE Cord)
60°C Black
Length : 2,997.2mm ±76mm
118" ±3"

| Connector Component | | |
|--|------|---------------|
| Instruction | Qty. | Colour |
| (IEC 60320, C13, 10A 250V) | 1 | 35p (Black) |
| 2.0 × 4.0 GEM 98740BS-0 (#16-18) (Receptacle Terminal) | 3 | Brass-Natural |
| GA005-5 (2.0×4.0 Serial Housing) | 1 | Off-White |

| Dimensions | | |
|------------|---------|------------------|
| ROJ | Strip | Colour |
| 16±1 | 5 +1/-0 | Brown (L) |
| 16±1 | 5 +1/-0 | Blue (N) |
| 16±1 | 5 +1/-0 | Green-Yellow (E) |

Dimensions : Millimetres

High Quality Power Cord

UL Certificated

Note:

1. Hi-Pot Test : 1,500V/1Sec; <0.5mA
2. Insulation Resistance Test : DC 500/min>100mΩ
3. Continuity & Polarization Test : No short circuit, break circuit, displacement.
4. Each end terminal shall be capable of withstanding a pull of 25lbs for 1 minutes without loosening.
5. Strain relief shall be capable of withstanding a pull of 35lbs for 1 minutes without loosening.
6. All material according to Non-toxic standard.



Part Number Table

| Description | Part Number |
|---|-----------------|
| 6-15P to C13, RA, SJT, CEE, 18×3C, 10A 250V | P11801US-SJT-10 |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.