

DIN-Signal coax m, Löt/crimp 50Ohm



Image is for illustration purposes only. Please refer to product description.

Part number	09 03 000 6167
Specification	DIN-Signal coax m, Löt/crimp 50Ohm
HARTING eCatalogue	https://b2b.harting.com/09030006167

Identification

Category	Contacts
Series	DIN 41612
Type of contact	Coaxial contact
Description of the contact	Straight
Contacts for	DIN 41612 Type M
Features	lead-free

Version

Termination method	PCB solder termination
Gender	Male contact for female connectors
Manufacturing process	Turned contacts

Technical characteristics

Rated voltage	250 V
Insulation resistance	$>10^9 \Omega$
Contact resistance	$\leq 10 \text{ m}\Omega$ for inner contact die $\leq 3 \text{ m}\Omega$ for outer ferrule
Impedance	50 Ω
Limiting temperature	-55 ... +125 °C
Insertion force	$\leq 10 \text{ N}$
Withdrawal force	$\geq 1 \text{ N}$
Performance level	1
Mating cycles	≥ 500



Pushing Performance
Since 1945

Technical characteristics

Test voltage $U_{r.m.s.}$ 0.75 kV

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni Mating side

Specifications and approvals

Specifications	DIN 41626
----------------	-----------

Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85369010
ETIM	EC000796
eCl@ss	27440204 Contact for industrial connectors