

Han-Fast Lock 4-6mm², Ag

	-	Part number	09 08 000 7923
		Specification	Han-Fast Lock 4-6mm², Ag
Identification			
Category	Contacts		
Series	Han-Fast [®] Lo	ock	
Type of contact	PCB contact		
Description of the contact	Without pin		
Version			
Pack contents	Single contac	t	
Technical characteristics			
Conductor cross-section	4 6 mm²		
Rated current	≤60 A		
Contact resistance	_00 / Λ ≤2 mΩ		
Stripping length	7.5 mm		
Material properties			
Material (contacts)	Copper alloy		
Surface (contacts)	Silver plated		
Material (locking)	Copper alloy		
Surface (locking)	Passivated		
RoHS	compliant		
ELV status	compliant		
China RoHS	е		
REACH Annex XVII substances	Not contained	b	
REACH ANNEX XIV substances	Not contained	b	

Page 1 / 2 | Creation date 2023-09-13 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
Specifications and approvals	
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
Commercial data	
Packaging size	100
Net weight	1.22 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140014893
ETIM	EC002637
eCl@ss	27460201 PCB connector (board connector)

Page 2 / 2 | Creation date 2023-09-13 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany