

Han 1A-3+PE-c-f



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 10 003 3306 |
| Specification | Han 1A-3+PE-c-f |
| HARTING eCatalogue | https://b2b.harting.com/09100033306 |

Identification

| | |
|----------|---------------------|
| Category | Inserts |
| Series | Han [®] 1A |

Version

| | |
|--------------------|---|
| Termination method | Crimp termination |
| Gender | Female |
| Size | 1 A |
| Number of contacts | 3 |
| PE contact | Yes |
| Locking type | Single locking lever |
| Details | Please order crimp contacts separately. Please order locking lever separately. Order separately the single wire seal or the hoods/housings for an IP65 performance. |

| | |
|---------|---|
| Details | A Han [®] 1A configuration that only consists of inserts (with or without strain relief, 09 10 000 5300) is an unenclosed connector according to IEC 61984. In this case protection against electric shock must be provided by the installation methods of the user. Contact inserts must not be coupled or decoupled under electrical load. Contact inserts must not be powered-up in the un-mated condition. |
|---------|---|

Technical characteristics

| | |
|-------------------------|----------------------------|
| Conductor cross-section | 0.14 ... 4 mm ² |
| Rated current | 16 A |
| Rated voltage | 400 V |
| Rated impulse voltage | 6 kV |



Pushing Performance
 Since 1945

Technical characteristics

| | |
|--|----------------|
| Pollution degree | 3 |
| Rated current acc. to UL | 15 A AWG 12 |
| Rated voltage acc. to UL | 600 V |
| Insulation resistance | $>10^8 \Omega$ |
| Limiting temperature | -30 ... +90 °C |
| Mating cycles | ≥ 100 |
| Degree of protection acc. to IEC 60529 | IP20 |

Material properties

| | |
|---|------------------------------|
| Material (insert) | Polyamide (PA) |
| Colour (insert) | RAL 9005 (jet black) |
| Material (seal) | NBR |
| Colour (seal) | Black |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Not contained |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| | |
|----------------|---|
| Specifications | EN 45545-2 Fire protection on railway vehicles IEC 61373 Category 1 Class B IEC 60664-1 IEC 61984 |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 Please contact your local HARTING subsidiary for further information. |
| Approvals | DNV GL |



Pushing Performance
Since 1945

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Net weight | 10 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140185470 |
| ETIM | EC000438 |
| eCl@ss | 27440205 Contact insert for industrial connectors |