

Han Q 8/0-agg vernickelt



Image is for illustration purposes only. Please refer to product description.

Part number	09 12 008 0303
Specification	Han Q 8/0-agg vernickelt
HARTING eCatalogue	https://b2b.harting.com/09120080303

Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Compact [®]
Type of hood/housing	Bulkhead mounted housing

Version

Size	Han-Compact [®]
Locking type	Single locking lever
Field of application	Hoods/Housings for higher EMC requirements

Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	12

Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Nickel plated
Material (seal)	NBR
Material (locking)	Stainless steel
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption



Pushing Performance
Since 1945

Material properties

China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	564b7d75-7bf6-4cfb-acb1-2168eb61b675
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076
	UL 2237 PVVA2.E318390
	CSA-C22.2 No. 182.3 ECBT8.E235076
	CSA-C22.2 No. 182.3 PVVA8.E318390
CE	Yes
Approvals	DNV GL

Commercial data

Packaging size	10
Net weight	55 g
Country of origin	Romania
European customs tariff number	85389099
GTIN	5713140017559
ETIM	EC000437
eCl@ss	27440202 Shell for industrial connectors