

Pneum. contact metal OD3mm female angled



Part number	09 14 000 7453
Specification	Pneum. contact metal OD3mm female angled
HARTING eCatalogue	https://b2b.harting.com/09140007453

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Contacts
Type of contact	Pneumatic contact
Description of the contact	Without shut-off
·	Angled
Features	The Han® Pneumatic contacts without shut-off are suitable for the use inside a vacuum. (Limit: 100 mbar = 100 hPa \approx approx 90% vacuum)
Version	
Gender	Female
Manufacturing process	Turned contacts
-	
Technical characteristics	
Limiting temperature	-20 +85 °C Tube outer diameter
Operating pressure	≤10 bar
Tube outer diameter	3 mm
Material properties	
Material (contacts)	Brass
Material (seal)	NBR
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained

Page 1 / 2 | Creation date 2023-09-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties REACH ANNEX XIV substances

Not contained

Yes

Lead

REACH SVHC substances

REACH SVHC substances

ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead
	Nickel

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076
	CSA-C22.2 No. 182.3 ECBT8.E235076

Commercial data

Packaging size	10
Net weight	12.3 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140189171
ETIM	EC000796
eCl@ss	27440204 Contact for industrial connectors