

## Han-Modular Compact carrier hood



Image is for illustration purposes only. Please refer to product description.

Part number	09 14 001 0311
Specification	Han-Modular Compact carrier hood
HARTING eCatalogue	<a href="https://b2b.harting.com/09140010311">https://b2b.harting.com/09140010311</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Modular <sup>®</sup> Compact
Type of hood/housing	Carrier hood

### Version

Size	Modular Compact
Locking type	Single locking lever
Details	Rated voltage $\leq 630$ V Rated impulse voltage $\leq 6$ kV Pollution degree 3 For a complete connector the specified voltage rating is the maximum level which can be achieved. In cases where the used module(s) do offer lower voltage ratings, then these lower ratings are valid. Higher voltage ratings in individual applications can be approved in coordination with HARTING.

### Technical characteristics

Stripping length	10 mm PE contact
Tightening torque	1 Nm PE screw
Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Mating cycles	$\geq 500$
Degree of protection acc. to IEC 60529	IP65 locked condition

### Material properties

Material (hood/housing)	Zinc die-cast
-------------------------	---------------



Pushing Performance  
Since 1945

## Material properties

Surface (hood/housing)	Nickel plated
Material (seal)	NBR
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead
California Proposition 65 substances	Nickel
California Proposition 65 substances	Naphthalene

## Specifications and approvals

Specifications	IEC 61984
CE	Yes

## Commercial data

Packaging size	1
Net weight	65 g
Country of origin	Romania
European customs tariff number	85389099
GTIN	5713140018983
ETIM	EC000437
eCl@ss	27440202 Shell for industrial connectors