


## Han SC module, female with metal ferrule



| Part number        | 09 14 004 4713                           |
|--------------------|--|
| Specification      | Han SC module, female with metal ferrule |
| HARTING eCatalogue | https://b2b.harting.com/09140044713      |

Image is for illustration purposes only. Please refer to product description.

| Identification  |  |
|---|--|
| Category  | Modules  |
| Series  | Han-Modular <sup>®</sup>   |
| Type of module  | Han <sup>®</sup> SC module   |
| Size of the module  | Single module  |
| Description of the module   | with metal ferrule   |
| Version   |  |
| Gender  | Female   |
| Number of contacts  | 4  |
| Details   | Please order contacts separately.  |
|   |  |
| Technical characteristics   |  |
| Technical characteristics<br>Limiting temperature   | -40 +85 °C   |
|   | -40 +85 °C<br>≥500   |
| Limiting temperature  |  |
| Limiting temperature<br>Mating cycles   |  |
| Limiting temperature<br>Mating cycles<br>Material properties  | ≥500   |
| Limiting temperature<br>Mating cycles<br>Material properties<br>Material (insert)   | ≥500<br>Polycarbonate (PC)   |
| Limiting temperature<br>Mating cycles<br>Material properties<br>Material (insert)<br>Colour (insert)  | ≥500<br>Polycarbonate (PC)<br>RAL 7032 (pebble grey)                     |
| Limiting temperature<br>Mating cycles<br>Material properties<br>Material (insert)<br>Colour (insert)<br>Material flammability class acc. to UL 94         | ≥500<br>Polycarbonate (PC)<br>RAL 7032 (pebble grey)<br>V-0              |
| Limiting temperature<br>Mating cycles<br>Material properties<br>Material (insert)<br>Colour (insert)<br>Material flammability class acc. to UL 94<br>RoHS | ≥500<br>Polycarbonate (PC)<br>RAL 7032 (pebble grey)<br>V-0<br>compliant |

Page 1 / 2 | Creation date 2023-08-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



## Material properties

| REACH ANNEX XIV substances           | Not contained                |
|--------------------------------------|------------------------------|
| REACH SVHC substances                | Not contained                |
| California Proposition 65 substances | Not contained                |
| Fire protection on railway vehicles  | EN 45545-2 (2020-08)         |
| Requirement set with Hazard Levels   | R22 (HL 1-3)<br>R23 (HL 1-3) |
| Specifications and approvals         |                              |
| Approvals                            | DNV GL                       |
| Commercial data                      |                              |
| Packaging size                       | 2                            |
| Net weight                           | 11 g                         |
| Country of origin                    | Germany                      |
| European customs tariff number       | 85389099                     |
| GTIN                                 | 5713140020221                |
|                                      | F 0000 (00                   |
| ETIM                                 | EC000438                     |