

Han-Mod RJ45 PreLink Set 8P AWG 22-23



Part number	09 14 008 4720
Specification	Han-Mod RJ45 PreLink Set 8P AWG 22-23
HARTING eCatalogue	https://b2b.harting.com/09140084720

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Inserts
Element	Data connectors
Specification	Han [®] RJ45 cable jack

Version

Termination method	preLink [®] IDC insulation displacement termination
Gender	Female
Number of contacts	8

Technical characteristics

Conductor cross-section	AWG 23 AWG 22
Wire outer diameter	1.3 1.6 mm
Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz
Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
Limiting temperature	-40 +70 °C
Mating cycles	≥500
Cable diameter	5 9 mm

Material properties

Material (insert) Polyamide (PA)	Polyamide (PA)
----------------------------------	----------------

Page 1 / 2 | Creation date 2023-08-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

Material (shielding)	Zinc die-cast, nickel-plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
Approvals	DNV GL

Commercial data

Packaging size	1
Net weight	23.52 g
Country of origin	Latvia
European customs tariff number	85389099
GTIN	5713140020795
ETIM	EC000438
eCl@ss	27440218 Module for industrial connectors (data)