

Pushing Performance Since 1945

Hinged frame 24B for 6 modules (A..F)



、 <i>、</i> /	
Part number	09 14 024 0303
Specification	Hinged frame 24B for 6 modules (AF)
HARTING eCatalogue	https://b2b.harting.com/09140240303

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Accessories
Series	Han-Modular [®]
Type of accessory	Hinged frame
Description of the accessory	for 6 modules A F
Features	Conductor cross-section PE (power side) 4 10 mm ² Conductor cross-section PE (signal side) 1 2.5 mm ²
Version	
Size	24 B
Technical characteristics	
Limiting temperature	-40 +125 °C
Mating cycles	≥500
Material properties	
Material	Zinc die-cast
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes

Page 1 / 2 | Creation date 2023-09-01 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Pushing Performance Since 1945

Material properties

REACH SVHC substances	Lead
ECHA SCIP number	564b7d75-7bf6-4cfb-acb1-2168eb61b675
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead
	Nickel

Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
UL / CSA	UL 1977 ECBT2.E235076
Approvals	DNV GL
Commercial data	
Packaging size	2
Net weight	76.5 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140021273
ETIM	EC002312
eCl@ss	27440206 Module carrier frame for industrial connectors