

R 15-GG



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 15 000 0401 |
| Specification | R 15-GG |
| HARTING eCatalogue | https://b2b.harting.com/09150000401 |

Identification

| | |
|----------------------|----------------|
| Category | Hoods/Housings |
| Series | R 15 |
| Type of hood/housing | Hood |

Version

| | |
|--------------|---------------|
| Cable entry | 1x Pg 11 |
| Locking type | Screw locking |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +125 °C |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP65 |

Material properties

| | |
|-------------------------------------|----------------------|
| Material (hood/housing) | Polycarbonate (PC) |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |



Pushing Performance
Since 1945

Material properties

| | |
|------------------------------------|------------------------------|
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |
|------------------------------------|------------------------------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 10 |
| Net weight | 19.16 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140021648 |
| ETIM | EC003556 |
| eCl@ss | 27440224 Shell for circular connectors |