

## M23 HMB angled



Image is for illustration purposes only. Please refer to product description.

Part number	09 15 100 0901
Specification	M23 HMB angled
HARTING eCatalogue	<a href="https://b2b.harting.com/09151000901">https://b2b.harting.com/09151000901</a>

### Version

Size	M23
Fixing	Fixing hole 4x 2.7 mm
Locking type	Screw locking ComLock rapid locking

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP67 locked condition IP69 / IPX9K acc. to ISO 20653 locked condition

### Material properties

Material (hood/housing)	Copper-zinc alloy
Surface (hood/housing)	Nickel plated
Material (seal)	NBR
Colour (seal)	Black
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes



Pushing Performance  
Since 1945

Material properties

California Proposition 65 substances	Lead
	Nickel

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076
----------	-----------------------

Commercial data

Packaging size	5
Net weight	76.3 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140184084
eCl@ss	27440224 Shell for circular connectors