

# Han D M crimp contact 2,5 mm<sup>2</sup> Au/HMC



Part number	09 15 200 6126
Specification	Han D M crimp contact 2,5 mm² Au/HMC
HARTING eCatalogue	https://b2b.harting.com/09152006126

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Contacts
Series	Han D <sup>®</sup> HMC
Type of contact	Crimp contact

#### Version

Manufacturing process Turned contacts	Gender	Male
	Manufacturing process	Turned contacts

#### Technical characteristics

Conductor cross-section	2.5 mm²
Conductor cross-section	AWG 14
Rated current	≤10 A
Contact resistance	≤3 mΩ
Stripping length	6 mm
Mating cycles with other HMC components	≥10,000

## Material properties

Material (contacts)	Copper alloy
Surface (contacts)	HMC gold plated
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50



# Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

Charifications	IEC 60664-1
Specifications	IEC 61984

### Commercial data

Packaging size	100
Net weight	0.6 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140023000
ETIM	EC000796
eCl@ss	27440204 Contact for industrial connectors