This product is not orderable anymore. Please contact your local distribution partner.



SEK-18 SV MA STD ANG29 RKZ 06PPLS4CLIP




Image is for illustration purposes only. Please refer to product description.

Part number 09 18 506 5963

Specification SEK-18 SV MA STD ANG29 RKZ 06PPLS4CLIP

Identification

Category	Connectors
Series	SEK Standard
Element	Male connector
Description of the contact	Angled

Version

Termination method	Wave soldering termination
Connection type	PCB to cable
Number of contacts	6
Termination length	2.9 mm
PCB fixing	With board locks
Locking type	With short levers

Technical characteristics

Contact rows	2
Contact spacing (termination side)	2.54 mm
Rated current	1 A
Insulation resistance	>10 ⁹ Ω
Contact resistance	≤20 mΩ
Limiting temperature	-55 +125 °C
Performance level	NM 30 (S4)
Mating cycles	≥250
Test voltage U _{r.m.s.}	1 kV

This product is not orderable anymore. Please contact your local distribution partner.



Technical characteristics

Isolation group IIIa (175 ≤ CTI < 400)

PCB thickness 1.6 mm

Material properties

Material (insert)	Thermoplastic resin (PBT)
Colour (insert)	Grey
Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni Mating side Sn over Ni Termination side
Layer thickness	≥0.76 µm
Layer thickness	≥30 µinch
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained


Specifications and approvals

Specifications	IEC 60603-13
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
Railway classification	F3/I3

Commercial data

Packaging size	1
eCl@ss	27460201 PCB connector (board connector)

Cross section of solder termination



Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com