


SEK-18 SV MA STD ANGWW RKZ 20P PLS4



| Image is for illustration | purposes only. | Please refer to | product description. |
|---------------------------|----------------|-----------------|----------------------|

| Part number | 09 18 520 5916 |
|--------------------|--|
| Specification | SEK-18 SV MA STD ANGWW RKZ 20P PLS4 |
| HARTING eCatalogue | https://b2b.harting.com/09185205916 |

Identification

| Category | Connectors |
|----------------------------|----------------|
| Series | SEK Standard |
| Element | Male connector |
| Description of the contact | Angled |

Version

| Termination method | Wrap termination |
|--------------------|-------------------|
| Connection type | PCB to cable |
| Number of contacts | 20 |
| Termination length | 15 mm |
| Locking type | With short levers |

Technical characteristics

| Dimensions wire wrap post | 0.6 x 0.6 mm |
|------------------------------------|--------------------|
| Contact rows | 2 |
| Contact spacing (termination side) | 2.54 mm |
| Rated current | 1 A |
| Insulation resistance | >10 ⁹ Ω |
| Contact resistance | ≤20 mΩ |
| Limiting temperature | -55 +125 °C |
| Performance level | NM 30 (S4) |
| Mating cycles | ≥250 |
| Test voltage U _{r.m.s.} | 1 kV |

This product is not orderable anymore. Please contact your local distribution partner.



Technical characteristics

| Isolation group | IIIa (175 ≤ CTI < 400) |
|-----------------|------------------------|
|-----------------|------------------------|

Material properties

| Material (insert) | Thermoplastic resin (PBT) |
|---|---|
| Colour (insert) | Grey |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Noble metal over Ni Mating side Sn over Ni Termination side |
| Layer thickness | ≥0.76 µm |
| Layer thickness | ≥30 µinch |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Antimony trioxide Lead Nickel |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| Specifications | IEC 60603-13 |
|------------------------|--|
| UL / CSA | UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079 |
| Railway classification | F3/I3 |

Commercial data

| Packaging size | 100 |
|--------------------------------|---------------|
| Net weight | 13.1 g |
| Country of origin | Switzerland |
| European customs tariff number | 85366990 |
| GTIN | 5713140029668 |

Product data sheet 09 18 520 5916 SEK-18 SV MA STD ANGWW RKZ 20P PLS4

This product is not orderable anymore. Please contact your local distribution partner.



Commercial data

eCl@ss

27460201 PCB connector (board connector)

Cross section of solder termination

