

## Han 16B-HSE-NPTF 3/4 Zoll

		Part number	09 30 516 1520
		Specification	Han 16B-HSE-NPTF 3/4 Zoll
Identification			
Category	Hoods/Housir	ngs	
Series of hoods/housings	Han <sup>®</sup> B	-	
Type of hood/housing	Hood		
Туре	Low construct	ion	
Version			
Size	16 B		
Version	Side entry		
Cable entry	1x NPTF 3/4"		
Locking type	Double locking lever		
Field of application	Standard hoo	ds/housings for industrial o	connectors
Technical characteristics			
	-40 +125 °C		
Limiting temperature Note on the limiting temperature		connector according to IEC	C 61094
Degree of protection acc. to IEC 60529	IP65		5 0 1904.
Degree of protection acc. to fee 00529	IF00		
Material properties			
Material (hood/housing)	Aluminium die	e-cast	
Surface (hood/housing)	Powder-coated		
Colour (hood/housing)	RAL 7037 (du	st grey)	
RoHS	compliant		
ELV status	compliant		
China RoHS	е		

Page 1 / 2 | Creation date 2023-08-22 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



## Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R1 (HL 1-3) R7 (HL 1-3)

## Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes
Approvals	DNV GL
Commercial data	
Packaging size	1
Net weight	195 g
Country of origin	China
ETIM	EC000437
eCl@ss	27440202 Shell for industrial connectors