

# Han PP PFT met. circular Bulkhead Cat.6A



Part number	09 35 225 0312
Specification	Han PP PFT met. circular Bulkhead Cat.6A
HARTING eCatalogue	https://b2b.harting.com/09352250312

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Connectors
Series	Han <sup>®</sup> PushPull (V14)
Identification	RJ45
Element	Panel feed trough set
Specification	AIDA compliant
Features	Intuitive locking mechanism
Version	
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8
Fixing	Screwable to cover plates
Locking type	PushPull
Pack contents	inkl. bulkhead mounted housing for circular panel cut out, flat seal and HARTING RJ Industrial $^{\textcircled{B}}$ 10G RJ45 bulkhead
Technical characteristics	

# Conductor cross-section0.22 ... 0.32 mm² Stranded<br/>0.26 ... 0.32 mm² SolidRated current1.75 ARated voltage50 VTransmission characteristicsCat. 6A Class EA up to 500 MHz

Page 1 / 3 | Creation date 2023-09-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



### **Technical characteristics**

Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
Limiting temperature	-40 +70 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65
	IP67

# Material properties

Surface (contacts)	Au over Ni Mating side
Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Nickel plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide Lead Nickel

## Specifications and approvals

Specifications	IEC 61076-3-117 Variant 14 (V14) IEC 60603-7 Mating face EN 45545-2
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
Approvals	DNV GL
PROFINET	Yes

Page 2 / 3 | Creation date 2023-09-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



### Commercial data

Packaging size	1
Net weight	6 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140054011
ETIM	EC002636
eCl@ss	27440114 Rectangular connector (for field assembly)

Page 3 / 3 | Creation date 2023-09-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany