

## PP-V14-CC-IDC-RJ45-4P-P-M-STR-SHLD



Image is for illustration purposes only. Please refer to product description.

Part number	09 35 229 0401
Specification	PP-V14-CC-IDC-RJ45-4P-P-M-STR-SHLD
HARTING eCatalogue	<a href="https://b2b.harting.com/09352290401">https://b2b.harting.com/09352290401</a>

### Identification

Category	Connectors
Series	Han <sup>®</sup> PushPull (V14)
Element	Connector
Specification	AIDA compliant PROFINET Multi Feature RJ45 Straight
Features	Suitable for all PoE versions

### Version

Termination method	IDC termination
Shielding	Fully shielded, 360° shielding contact
Number of contacts	4
Coding	RJ45
Details	When installing a PROFINET system, observe the PROFINET installation guideline.

### Technical characteristics

Conductor cross-section	0.12 ... 0.32 mm <sup>2</sup> Stranded 0.12 ... 0.32 mm <sup>2</sup> Solid
Conductor cross-section	AWG 26/7 ... AWG 22/7 Stranded AWG 24/1 ... AWG 22/1 Solid
Wire outer diameter	0.8 ... 1.6 mm
Transmission characteristics	Cat. 5 Class D up to 100 MHz



Pushing Performance  
Since 1945

## Technical characteristics

Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 ... +85 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65 IP67
Cable diameter	5 ... 8 mm
Vibration resistance	10-500 Hz, 0.35 mm / 50 m/s <sup>2</sup> , 2h/Achse 5.72 m/s <sup>2</sup> acc. to IEC 61373 Category 1 Class B
Shock resistance	50 g / 30 ms, 3 shocks / axis and direction acc. to IEC 61373 Category 1 Class B

## Material properties

Surface (contacts)	Au over Ni Mating side Sn over Ni Termination side
Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Nickel plated
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

## Specifications and approvals

Specifications	IEC 60603-7 Mating face ISO/IEC 11801 EN 50173-1 IEC 61076-3-117 Variant 14
Approvals	DNV GL
PROFINET	Yes

## Commercial data

Packaging size	1
Country of origin	Latvia
European customs tariff number	85366990



**Pushing Performance**  
Since 1945

## Commercial data

GTIN	5713140224292
ETIM	EC002636
eCl@ss	27440114 Rectangular connector (for field assembly)

---