

## Han PP Power L plug metal var.coding



Image is for illustration purposes only. Please refer to product description.

Part number	09 35 432 0401
Specification	Han PP Power L plug metal var.coding
HARTING eCatalogue	<a href="https://b2b.harting.com/09354320401">https://b2b.harting.com/09354320401</a>

### Identification

Category	Connectors
Series	Han <sup>®</sup> PushPull (V14)
Identification	Power L
Element	Connector sets
Specification	AIDA compliant Finger safe Variable coding
Features	Intuitive locking mechanism field assembly without tools

### Version

Termination method	Spring clamp termination
Shielding	Unshielded
Number of contacts	5
Locking type	PushPull

### Technical characteristics

Conductor cross-section	0.75 ... 2.5 mm <sup>2</sup>
Conductor cross-section	AWG 18 ... AWG 13
Rated current	16 A
Rated voltage	24 V
Rated impulse voltage	4 kV
Pollution degree	3



**Pushing Performance**  
Since 1945

## Technical characteristics

Stripping length	10 mm Conductors 44 mm cable jacket
Tightening torque	3 Nm
Limiting temperature	-40 ... +70 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 IP67
Cable diameter	9 ... 13 mm

## Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Au over Ni Mating side Sn over Ni Termination side
Material (hood/housing)	Metal
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

Specifications	IEC 61076-3-117 Variant 14 (V14)
UL / CSA	UL 1059 XCFR2.E314677 CSA-C22.2 No. 158-10 XCFR8.E314677
Approvals	DNV GL
PROFINET	Yes

## Commercial data

Packaging size	1
Net weight	95.4 g
Country of origin	Germany



**Pushing Performance**  
Since 1945

## Commercial data

European customs tariff number	85366990
GTIN	5713140054554
ETIM	EC002636
eCl@ss	27440114 Rectangular connector (for field assembly)