

## HPP V4 USB 3.0 A, EI-PFT



Image is for illustration purposes only. Please refer to product description.

Part number	09 45 245 1905
Specification	HPP V4 USB 3.0 A, EI-PFT
HARTING eCatalogue	<a href="https://b2b.harting.com/09452451905">https://b2b.harting.com/09452451905</a>

### Identification

Category	Connectors
Series	HARTING PushPull (V4)
Identification	USB
Element	Panel feed through
Specification	USB 3.0 type A
Description of hood/housing	EasyInstall

### Version

Shielding	Fully shielded, 360° shielding contact
Number of contacts	4

### Technical characteristics

Limiting temperature	-40 ... +70 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65 IP67

### Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Naphthalene

## Specifications and approvals

Specifications	IEC 61076-3-106 Variant 4 (V4) EN 45545-2
Approvals	DNV GL

## Commercial data

Packaging size	1
Net weight	18 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140059924
eCl@ss	27440114 Rectangular connector (for field assembly)