

# RJI RJ45 PN Cat.5, 4p jack IDC AWG24-22



Part number 09 45 545 1120

Specification RJI RJ45 PN Cat.5, 4p jack IDC AWG24-22

HARTING eCatalogue https://b2b.harting.com/09455451120

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Connectors
Series	HARTING RJ Industrial <sup>®</sup>
Element	Female
Specification	RJ45
	HIFF version

#### Version

Termination method	IDC termination
Shielding	Fully shielded, 360° shielding contact
Number of contacts	4

#### Technical characteristics

Conductor cross-section	0.22 0.32 mm² solid and stranded
Conductor cross-section	AWG 24 AWG 22
Wire outer diameter	1.7 mm
Rated current	1.76 A
Rated voltage	50 V AC 60 V DC
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 +70 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP20

Page 1 / 2 | Creation date 2023-08-26 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



## Technical characteristics

Cable diameter 5 9 mm
-----------------------

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	White Yellow
Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Nickel plated
Material flammability class acc. to UL 94	V-2
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

# Specifications and approvals

Approvals	DNV GL
PROFINET	Yes

## Commercial data

Packaging size	1
Net weight	10 g
Country of origin	Latvia
European customs tariff number	85366990
GTIN	5713140061163
ETIM	EC000438
eCl@ss	27440205 Contact insert for industrial connectors