

## RJI RJ45 jack Cat.5 THR vertical 16x16




Image is for illustration purposes only. Please refer to product description.

Part number	09 45 551 1120
Specification	RJI RJ45 jack Cat.5 THR vertical 16x16
HARTING eCatalogue	<a href="https://b2b.harting.com/09455511120">https://b2b.harting.com/09455511120</a>

### Identification

Category	Connectors
Series	HARTING RJ Industrial®
Element	Female
Specification	RJ45 Without LED Vertical With contact spring

### Version

Termination method	Reflow soldering termination (THR)
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8
Pack contents	Tray

### Technical characteristics

Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s
Limiting temperature	-40 ... +85 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP20



**Pushing Performance**  
Since 1945

## Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

## Specifications and approvals

UL / CSA	UL 1977 DUXR2.E254191 CSA-C22.2 No. 182.4, No. 233-09 DUXR8.E254191
Approvals	DNV GL

## Commercial data

Packaging size	60
Net weight	6 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140061569
ETIM	EC002637
eCl@ss	27460201 PCB connector (board connector)