

# Han 3A-Base angled-M25



Part number	19 20 003 1165
Specification	Han 3A-Base angled-M25
HARTING eCatalogue	https://b2b.harting.com/19200031165

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Hoods/Housings
Series of hoods/housings	Han A <sup>®</sup>
Type of hood/housing	Screw mounted housing
Description of hood/housing	Angled

#### Version

Size	3 A
Cable entry	1x M25
Locking type	Single locking lever
Field of application	Standard Hoods/housings for industrial applications
Pack contents	Please order seal screw separately.

## Technical characteristics

Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP44 IP65 With seal screw IP67 With seal screw
Type rating acc. to UL 50 / UL 50E	12

#### Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)

Page 1 / 2 | Creation date 2023-08-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



#### Material properties

c plated
c plateu
npliant with exemption
) / 6(a)-l: Lead as an alloying element in steel for machining purposes and galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying ment in steel for machining purposes containing up to 0,35 % lead by weight d in batch hot dip galvanised steel components containing up to 0,2 % lead by ght
): Copper alloy containing up to 4 % lead by weight
npliant with exemption
contained
contained
3
ad
3
kel phthalene
45545-2 (2020-08)
(HL 1-3) (HL 1-3)

## Specifications and approvals

CE	Yes
Approvals	DNV GL

## Commercial data

Packaging size	10
Net weight	101.88 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140164062
ETIM	EC000437
eCl@ss	27440202 Shell for industrial connectors