

Han High Temp 10B-HSM-2xM32



Part number	19 62 810 0292
Specification	Han High Temp 10B-HSM-2xM32
HARTING eCatalogue	https://b2b.harting.com/19628100292

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] High Temp
Type of hood/housing	Surface mounted housing
Туре	High construction
Version	

Size	10 B
Version	Side entry
Cable entry	2x M32
Locking type	Double locking lever

Technical characteristics

Limiting temperature	-40 +200 °C With Han® High Temp components
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Uncoated
Colour (hood/housing)	Unpainted
Material (seal)	FPM
Colour (seal)	Red
Material (locking)	Stainless steel

Page 1 / 2 | Creation date 2023-08-30 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel
Commercial data	

Packaging size	1
Net weight	357.3 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140132689
ETIM	EC000437
eCl@ss	27440202 Shell for industrial connectors