

HAIIC MICA USB STARTERKIT



Image is for illustration purposes only. Please refer to product description.

Part number	20 95 000 0002 01
Specification	HAIIC MICA USB STARTERKIT
HARTING eCatalogue	https://b2b.harting.com/2095000000201

Identification

Series	HARTING IIC
Element	MICA
Specification	USB
Features	Designed for the harsh industrial environment Tested according industry and railway standards Ready for software customisation Adaptable, upgradeable hardware Power over Ethernet (PoE)

Version

Processor	1 GHz ARM
Memory	1 GB RAM 4 GB eMMC Up to 32 GB Flash (via Micro SD Card)
Operating system	Linux
Fixing	DIN rail mounting kit Wall mounting kit
Diagnostic display	2 LEDs to visualise the device status
Pack contents	2095000000200, HAIIC MICA USB 09488223756010, M12 X coded PushPull Cable Assembly, 1m 21348400C79010, M12 Cable Assembly A-cod st/- m/- 1 m 09451451912, HPP V4 USB 2.0 type A ; PP - IP20; 1,5m

Termination data

Supply voltage	12 V DC 24 V DC
----------------	--------------------



Termination data

Interfaces	Ethernet (TCP/IP) 10/100 Mbit/s
------------	---------------------------------

Technical characteristics

Limiting temperature	-25 ... +75 °C
Storage temperature	-25 ... +85 °C
Relative humidity	5 ... 95 % Non-condensing

Material properties

Material (hood/housing)	Aluminium
Surface (hood/housing)	Powder-coated
Length	132 mm
Width	86 mm
Height	35 mm
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

Specifications and approvals

Specifications	EN 301489
CE	Yes

Commercial data

Packaging size	1
Net weight	988 g
Country of origin	Germany
European customs tariff number	84714100
eCl@ss	90909090 Interim classification (unspecified)