

HAIIC MICA Wireless IO-Link 3p



Part number	20 95 000 0029 00
Specification	HAIIC MICA Wireless IO-Link 3p
HARTING eCatalogue	https://b2b.harting.com/2095000002900

Image is for illustration purposes only. Please refer to product description.

Identification	
Series	HARTING IIC
Element	MICA
Specification	Wireless IO Link 3p M8
Version	
Processor	Dual core 1.3 GHz ARM
Memory	2 GB RAM 16 GB eMMC
Fixing	On-wall or DIN rail mounting
Diagnostic display	LEDs to display operating state LEDs to display connection status
Termination data	
Termination data Supply voltage	24 V DC
	24 V DC GPS GSM: 2G/3G/4G WiFi: 802.11a/b/g/n WPA/WPA2 Enterprise Bluetooth: BLE 4.0 2 M8 24 V power supplies 3 M8 connectors for Class A IO Link devices
Supply voltage	GPS GSM: 2G/3G/4G WiFi: 802.11a/b/g/n WPA/WPA2 Enterprise Bluetooth: BLE 4.0 2 M8 24 V power supplies
Supply voltage	GPS GSM: 2G/3G/4G WiFi: 802.11a/b/g/n WPA/WPA2 Enterprise Bluetooth: BLE 4.0 2 M8 24 V power supplies

Page 1 / 2 | Creation date 2023-03-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING IT Software Development GmbH & Co. KG | Marienwerderstraße 2 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | Auto-ID@HARTING.com / MICASupport@harting.com | www.HARTING.com



Technical characteristics

Relative humidity	5 95 % Non-condensing
Degree of protection acc. to IEC 60529	IP67

Material properties

Material (hood/housing)	Aluminium
Surface (hood/housing)	Powder-coated
Length	132 mm
Width	86 mm
Height	35 mm

Specifications and approvals

Specifications	Directive 2014/30/EU Directive 2011/65/EU

Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	90909090 Interim classification (unspecified)