

## M12 Wanddurchführung 5pol./B-kod.



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 21 03 330 1300  |
| Specification      | M12 Wanddurchführung 5pol./B-kod.   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/21033301300">https://b2b.harting.com/21033301300</a> |

### Identification

|                   |                                   |
|-------------------|-----------------------------------|
| Category          | Accessories                       |
| Series            | Circular connectors M12           |
| Connector 1       | M12 B-coding<br>Female<br>5 poles |
| Type of accessory | Panel feed through                |

### Version

|        |          |
|--------|----------|
| Gender | Male     |
| Coding | B-coding |

### Technical characteristics

|  |                      |
|--|----------------------|
| Rated current                          | 4 A                  |
| Rated voltage                          | 60 V                 |
| Limiting temperature                   | -25 ... +85 °C       |
| Mating cycles                          | ≥100                 |
| Degree of protection acc. to IEC 60529 | IP67 mated condition |
| Thickness of the panel                 | 2 ... 5 mm           |

### Material properties

|                         |                        |
|-------------------------|------------------------|
| Material (insert)       | Polyamide (PA)         |
| Material (contacts)     | Copper alloy           |
| Surface (contacts)      | Au over Ni Mating side |
| Material (hood/housing) | Brass                  |



Pushing Performance  
Since 1945

## Material properties

|   |  |
|---|--|
| Material flammability class acc. to UL 94 | V-0  |
| RoHS                                      | compliant with exemption                               |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                                | compliant with exemption                               |
| China RoHS                                | 50   |
| REACH Annex XVII substances               | Not contained  |
| REACH ANNEX XIV substances                | Not contained  |
| REACH SVHC substances                     | Yes  |
| REACH SVHC substances                     | Lead   |
| ECHA SCIP number                          | 0d7d3693-d625-47ab-934a-d241bf72c86e                   |
| California Proposition 65 substances      | Yes  |
| California Proposition 65 substances      | Lead   |

## Specifications and approvals

|                |                 |
|----------------|-----------------|
| Specifications | IEC 61076-2-101 |
|----------------|-----------------|

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 39 g                                       |
| Country of origin              | Czechia                                    |
| European customs tariff number | 85366990                                   |
| GTIN                           | 5713140137875                              |
| ETIM                           | EC002943                                   |
| eCl@ss                         | 27440292 Connector component (accessories) |